Product data sheet Characteristics

MPL64225

Meter center, MP Meter-Pak, 4 sockets, lever bypass, jaw release, 5 jaws, 600A bus, 225A max breaker rating, ringless



MainProductMeter CenterSocket Rating225 AMain TypeMain LugsNumber of Jaws5Number of Meter
Sockets4Socket TypeRingless

Complementary

Complementary		
Main Rating	400 A	
	600 A	
Bus Rating	600 A	
Certifications	UL Listed	
Туре	Meter-Pak	
Busbar Material	Aluminium: busbar	
Bypass Type	Lever bypass	
Enclosure Material	Steel	
Enclosure Rating	NEMA 3R	
Maximum Voltage Rating	120/240 V AC	
Mounting	Surface	
Phase	1 phase	
Service Feed Location	UG	
	ОН	
Wire Size	AWG 1/0600 kcmil 1 aluminium	
	AWG 1/0600 kcmil 1 copper	
Wire Configuration	3-wire	
Height	67.37 in (1711.20 mm)	
Width	35.37 in (898.40 mm)	
Depth	9.62 in (244.35 mm)	

Ordering and shipping details

Category	00021-METER-PAK
Discount Schedule	DE4
GTIN	785901336563
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	20.51 in (52.1 cm)
Package 1 Width	42.01 in (106.7 cm)
Package 1 Length	72.01 in (182.9 cm)
Package 1 Weight	267.00 lb(US) (121.109 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes

Contractual warranty

Contraction Warranty		
Warranty	18 months	