# Product data sheet Characteristics

# AP7901B Rack PDU, Switched, 1U, 20A, 120V, (8)5-20





#### Overview

Lead time	Usually in Stock	
-----------	------------------	--



#### Main

IVIAIII	
Main Input Voltage	100 V 120 V
PDU Type	Switched
Main Output Voltage	120 V
Input Connection Type	NEMA L5-20P
Number of rack unit	1U
Cable length	12 ft (3.66 m)
Number of cables	1
Provided Equipment	Cord retention bracket(s) Horizontal mounting brackets User Manual Installation guide

#### Physical

Black	
1.73 in (4.4 cm)	
17.52 in (44.5 cm)	
4.25 in (10.8 cm)	
5.00 lb(US) (2.27 kg)	
Front Rear	
No preference	
Rack-mounted	
Horizontal	

#### Input

16 A
100120 V
20 A
1900 VA
50/60 Hz

### Output

Number of power socket outlets	8 NEMA 5-20R
--------------------------------	--------------

	٠.		•				
(	.0	ın	to	rn	าล	n	ce

Product Certifications	cUL Listed[RETURN]CSA[RETURN]Industry Canada[RETURN]UL Listed
Standards	FCC Part 15 class A
	ICES-003
	UL 60950

### Environmental

Ambient Air Temperature for Operation	32113 °F (045 °C)
Relative Humidity	095 %
Operating altitude	010000 ft
Ambient Air Temperature for Storage	-13149 °F (-2565 °C)
Storage Relative Humidity	095 %
Storage altitude	050000 ft (0.0015240.00 m)

## Ordering and shipping details

GTIN	731304331575
------	--------------

## Packing Units

r doming office	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.76 in (7 cm)
Package 1 Width	13.50 in (34.3 cm)
Package 1 Length	18.50 in (47 cm)
Package 1 Weight	7.61 lb(US) (3.45 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Compliant with Exemptions	
Lead free	Yes	
Mercury free	Yes	
RoHS exemption information	₫Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	☑ End Of Life Information	
Optimized Energy Efficiency	Energy efficient product	
Take-back	Take-back program available	

## Contractual warranty

Warranty	2 years repair or replace