# **GS2AH130**

External rotary handle, TeSys GS, black handle, front mounting, 2 positions I-O, NEMA 3R, for GS 30 to 400A UL





#### Main Range of Product **TeSys** TeSys Range GS2AH Device short name **Product or Component** Rotary handle Type Range compatibility TeSys TeSys GS GS2EU[RETURN]TeSys TeSys GS GS2GU[RETURN]TeSys TeSys GS GS2JU[RETURN]TeSys TeSys GS GS2MU[RETURN]TeSys TeSys GS GS2QU Type of operating External frontal handle

Black

Grey

Complementary		
Handle positions	O-I	
Rotary handle padlocking	With	
Switch rated current	30 A 60 A 100 A 200 A 400 A	
Standards	UL CSA	
Net Weight	0.53 lb(US) (0.24 kg)	

Handle colour

colour

Handle front plate

# Environment NEMA Degree of Protection NEMA 3R/12

### Ordering and shipping details

Category	22640-IEC DISCONNECT-GS1,LK3
Discount Schedule	l11
GTIN	3389119411837
Returnability	Yes
Country of origin	TN

#### Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	2.56 in (6.500 cm)	
Package 1 Width	6.30 in (16.000 cm)	
Package 1 Length	6.34 in (16.100 cm)	
Package 1 Weight	8.71 oz (247.000 g)	
Unit Type of Package 2	S03	
Number of Units in Package 2	18	
Package 2 Height	11.81 in (30.000 cm)	

Package 2 Width	11.81 in (30.000 cm)	
Package 2 Length	15.75 in (40.000 cm)	
Package 2 Weight	10.54 lb(US) (4.779 kg)	
Offer Sustainability		
Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Styrene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant	
Toxic heavy metal free	Yes	
Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	

## Contractual warranty

RoHS exemption information

Environmental Disclosure

Circularity Profile

Warranty	18 months
----------	-----------

Product Environmental Profile

End Of Life Information

Yes