



Main

| | |
|----------------------|------------------|
| Marketing Trade Name | QO |
| Product Type | Load Center |
| Cover Type | Order separately |

Complementary

| | |
|--|------------------------------------|
| Tightening Torque | Cover 20 lb.in |
| PoN Convertible Mains (lugs) | PoN Convertible Mains (breaker) |
| Rated Current | 200 A |
| Number of Spaces | 42 |
| Max Short Circuit Current Rating | 22 kA |
| Maximum Number of Single Pole Circuits | 52 |
| Maximum Number of Tandem Breakers | 10 |
| Number of Phases | 1 phase |
| Voltage Rating | 120/240 V AC |
| Wire Size | AWG 4...300 kcmil aluminium/copper |
| Ground Bar | Grounding bar (ordered separately) |
| Electrical Connection | Lugs |
| Wiring Configuration | 3-wire |
| Busbar Material | Tin plated copper: busbar |
| Enclosure Material | Welded sheet steel |
| Surface Finish | Baked enamel Gray |
| Box Number | 11 |
| Height | 37.99 in (965 mm) |
| Width | 14.25 in (362 mm) |

Environment

| | |
|---------------------------------------|---------------------------------|
| Enclosure Rating | NEMA 1 indoor |
| Ambient Air Temperature for Operation | 23 °F (-5 °C) 104 °F (40 °C) |
| Product Certifications | UL Listed |

Ordering and shipping details

| | |
|-------------------|--------------------------------------|
| Category | 10001-QO PON 1PH LC,12-60 CKT, MB N1 |
| Discount Schedule | DE3A |
| GTIN | 785901324386 |
| Returnability | Yes |
| Country of origin | US |

Packing Units

| | |
|------------------------------|----------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 4.30 in (10.922 cm) |
| Package 1 Width | 14.80 in (37.592 cm) |
| Package 1 Length | 38.70 in (98.298 cm) |
| Package 1 Weight | 22.35 lb(US) (10.138 kg) |
| Unit Type of Package 2 | PAL |
| Number of Units in Package 2 | 27 |
| Package 2 Height | 43.50 in (110.49 cm) |
| Package 2 Width | 40.00 in (101.6 cm) |
| Package 2 Length | 48.00 in (121.92 cm) |
| Package 2 Weight | 639.00 lb(US) (289.845 kg) |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | No need of specific recycling operations |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|