8502SFO3V02S

NEMA Contactor, Type S, nonreversing, Size 4, 135A, 100HP at 575VAC, 3 phase, up to 100kA, 4 pole, 120VAC coil, open



Main

Product Type	Contactor
Product Range	8502S
Contactor Type	Non-reversing

Complementary

4	
135 A	
4P	
600 V AC	
3 phase	
40 HP 200 V AC 50 HP 230 V AC 100 HP 460 V AC 100 HP 575 V AC	
Circuit-breaker 225 A maximum, SCCR: 100 kA at 480 V AC Fuse J 200 A maximum, SCCR: 100 kA at 600 V AC Fuse T 200 A maximum, SCCR: 100 kA at 600 V AC Fuse RK1 200 A maximum, SCCR: 100 kA at 600 V AC Fuse RK5 200 A maximum, SCCR: 100 kA at 600 V AC	
120 V AC 60 Hz 110 V AC 50 Hz	
Separate control circuit	
No control units	
No indicator	
Without	
Fuse not supplied	
Screw clamp terminals	
8.19 in (208.03 mm)	
9.75 in (247.65 mm)	
6.50 in (165.10 mm)	
	135 A 4P 600 V AC 3 phase 40 HP 200 V AC 50 HP 230 V AC 100 HP 460 V AC 100 HP 575 V AC Circuit-breaker 225 A maximum, SCCR: 100 kA at 480 V AC Fuse J 200 A maximum, SCCR: 100 kA at 600 V AC Fuse T 200 A maximum, SCCR: 100 kA at 600 V AC Fuse RK1 200 A maximum, SCCR: 100 kA at 600 V AC Fuse RK5 200 A maximum, SCCR: 100 kA at 600 V AC Fuse RK5 200 A maximum, SCCR: 100 kA at 600 V AC 120 V AC 60 Hz 110 V AC 50 Hz Separate control circuit No control units No indicator Without Fuse not supplied Screw clamp terminals 8.19 in (208.03 mm) 9.75 in (247.65 mm)

Environmental

Enclosure Type	Not rated (open device)
Certifications	UL listed file E78351 CCN NLDX[RETURN]CSA

Ordering and shipping details

Category	21193-8502,36 SE,SF(NOT S*R,T,W)	
Discount Schedule	CP1	
GTIN	785901608202	
Returnability	No	
Country of origin	MX	

Packing Units

3	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.19 in (20.8 cm)
Package 1 Width	9.76 in (24.8 cm)
Package 1 Length	6.50 in (16.5 cm)
Package 1 Weight	18.00 lb(US) (8.165 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	☑ China RoHS Declaration

Contractual warranty

Warranty	19 months
vvarianty	18 months