



Main

| | |
|-----------------------------|---------------------------|
| Product or Component Type | Miniature circuit-breaker |
| Range of Product | QOU |
| Circuit breaker type | Standard |
| Circuit breaker application | HACR rated |

Complementary

| | |
|--------------------------------|--|
| Line Rated Current | 25 A |
| Electrical connection | Ring tongue, line side Ring tongue, load side |
| [Ue] rated operational voltage | 120/240 V AC 240 V AC 120 V AC 48 V DC |
| Mounting Mode | Unit mount |
| AWG gauge | AWG 14...AWG 2 aluminium/copper |
| Height | 4.05 in (102.87 mm) |
| Width | 2.25 in (57.15 mm) |
| Depth | 2.95 in (74.93 mm) |
| Tightening torque | 45 lbf.in (5.08 N.m) (AWG 14...AWG 2) |

Environment

| | |
|------------------------|---------------------------------|
| Product Certifications | UL Listed[RETURN]IEC[RETURN]CSA |
|------------------------|---------------------------------|




Ordering and shipping details

| | |
|-------------------|-----------------------------|
| Category | 00900-QOU BREAKERS & SWITCH |
| Discount Schedule | DE2 |
| GTIN | 785901683797 |
| Returnability | No |
| Country of origin | MX |

Packing Units

| | |
|------------------------------|---------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 3.30 in (8.382 cm) |
| Package 1 Width | 2.90 in (7.366 cm) |
| Package 1 Length | 4.90 in (12.446 cm) |
| Package 1 Weight | 18.24 oz (517.0 g) |

Offer Sustainability

| | |
|-----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation |  REACH Declaration |
| EU RoHS Directive | Compliant with Exemptions |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation |  China RoHS Declaration |
| RoHS exemption information |  Yes |
| Circularity Profile | No need of specific recycling operations |
| Halogen content performance | Halogen free product |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|