# 9001KT38LGG9

Push-to-test pilot light, Harmony 9001K, metal, polycarbonate, domed, green, 30mm, LED green, 120V





#### Main

IVIAIII	
Range of Product	Harmony 9001K
Product or Component Type	Push-to-test pilot light
Device short name	К

Complementary

Complementary	
Bezel material	Metal
Mounting diameter	1.18 in (30 mm)
Lens type	Domed plastic
Cap/operator or lens colour	Green
Light source	Green LED
Bulb base	BA 9s
Light block supply	Direct 120 V
Shape of screw head	Round
Light source	LED
Operating Mode	Push-to-test
Lens type	Domed
[Us] rated supply voltage	120 V
Light source colour	Green
Contacts type and composition	1 C/O
Lens material	Polycarbonate
Size	30 mm

#### Environment

Product Certifications	CSA LR25490 class 3211 03[RETURN]UL listed file E42259 CCN NKCR[RETURN]CE
NEMA degree of protection	NEMA 1/2/3/3R/4/6/12/13

#### Ordering and shipping details

Category	21426-9001 K (NOT KA,KM,KX)
Discount Schedule	CS1
GTIN	785901036180
Returnability	No
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	5.08 in (12.903 cm)	
Package 1 Width	2.00 in (5.08 cm)	
Package 1 Length	12.90 in (32.774 cm)	
Package 1 Weight	6.40 oz (181.437 g)	

### Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	<sup>™</sup> China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations Circularity Profile
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

#### Contractual warranty

Contraction warranty		
Warranty	18 months	