# 1007003C

Meter socket, ringless, 3 phase, 4 wire, 20A, 13 jaws, 600VAC max, solid top, no bypass, no jaw release



Main	
Product or Component Type	Meter Socket
Meter socket type	Ringless
Hub type	Solid top

Complementary

Meter socket rated current	20.4	
Meter socket rated current	20 A	
Number of jaws	13 without jaw release	
Bypass type	No bypass	
Phase	3 phase	
[Ue] rated operational voltage	600 V AC	
Enclosure Material	Steel	
Electrical connection	Lugs slotted	
Service feed location	UG	
Wiring configuration	4-wire	
Device mounting	Surface	
AWG gauge	AWG 14AWG 2/0 aluminium/copper)line side AWG 14AWG 2/0 aluminium/copper)service ground	

#### Environment

Product Certifications	UL Listed
Enclosure Rating	NEMA 3R

## Ordering and shipping details

Category	00039-METER SOCKETS & HUBS
Discount Schedule	DE4
GTIN	785901542179
Returnability	Yes
Country of origin	US

#### **Packing Units**

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	4.60 in (11.684 cm)	
Package 1 Width	14.80 in (37.592 cm)	
Package 1 Length	17.30 in (43.942 cm)	
Package 1 Weight	19.42 lb(US) (8.809 kg)	
	. , , , , , , , , , , , , , , , , , , ,	

### Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Nickel (Metallic), which is known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Under investigation
Contractual warranty	
Warranty	18 months