

Product data sheet

Characteristics

MPZB15T2F25K

Unit substation, Mini Power-Zone, bolt on, 15kVA, 3 phase, 480V primary, 208Y/120V secondary, 25kA, CC



Main

Product	Sealed Transformer
Certifications	UL Listed
Type	Mini Power-Zone
Enclosure Code	CC
Insulation Temperature	365 °F (185 °C)
Phase	3 phase
Primary Voltage	480 V
Secondary Voltage	208Y/120 V
Full Capacity Taps	2 5 % FCBN
Power Rating	15 kVA
Temperature Rise	115 °C
Winding Material	Copper
Interrupt Rating	25 kA
Circuit Breaker Type	FAL34040 primary main breaker 40 A QO360 secondary main breaker 60 A QO/QOB feeder breaker 40 A
Interior Type	NQ Panelboard interior
Number of Spaces Available	27
Number of Circuits	27
Enclosure Type	NEMA 3R hot-rolled steel

Ordering and shipping details


Category	16276-MPZ BOLT-ON BRANCH CB
Discount Schedule	PE2
GTIN	785901460985
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	14.49 in (36.8 cm)
Package 1 Width	29.13 in (74.0 cm)
Package 1 Length	51.26 in (130.2 cm)
Package 1 Weight	550.00 lb(US) (249.476 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Nickel (Metallic), which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
RECh Regulation	RECh Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration

RoHS exemption information	 Yes
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------
