# Product data sheet Characteristics

# AP7801B Rack PDU, Metered, 1U, 20A, 120V, (8) 5-20



#### Overview

Lead time	Usually in Stock
	•



#### Main

Main Input Voltage	100 V	
	120 V	
PDU Type	Metered	
Main Output Voltage	120 V	
Input Connection Type	NEMA L5-20P	
Number of rack unit	1U	
Cable length	12 ft (3.66 m)	
Number of cables	1	
Provided Equipment	Cord retention bracket(s)	
	Installation guide	
	Rack Mounting brackets	
	User Manual	

#### **Physical**

Height	1.73 in (4.4 cm)	
Width	17.48 in (44.4 cm)	
Depth	4.02 in (10.2 cm)	
Net Weight	3.81 lb(US) (1.73 kg)	
Mounting Location	Front Rear	
Mounting preference	No preference	
Mounting Mode	Rack-mounted	
Mounting position	Horizontal	

## Input

Line Rated Current	16 A	
Input current limits	20 A	
Load Capacity	1920 VA	
Input Frequency	50/60 Hz	

#### Output

Number of power socket outlets 8 NEMA 5-20R	

## Conformance

Product Certifications	cUL Listed[RETURN]CSA[RETURN]UL Listed
Standards	FCC Part 15 class A ICES-003 UL 60950

## Environmental

Ambient Air Temperature for Operation	23113 °F (-545 °C)
Relative Humidity	595 %
Operating altitude	010000 ft
Ambient Air Temperature for Storage	-13149 °F (-2565 °C)
Storage Relative Humidity	595 %
Storage altitude	050000 ft (0.0015240.00 m)

# Ordering and shipping details

Category	80230-IG SEBA TO SEUSA
Discount Schedule	BMS1
GTIN	731304331469
Returnability	No
Country of origin	PH

## Packing Units

PCE
1
2.52 in (6.4 cm)
13.27 in (33.7 cm)
18.50 in (47 cm)
6.42 lb(US) (2.91 kg)

## Offer Sustainability

REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant with Exemptions
Lead free	Yes
Mercury free	Yes
RoHS exemption information	₫Yes
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

## Contractual warranty

	· · · · · · · · · · · · · · · · · · ·
Warranty	2 years repair or replace