


Product data sheet

Characteristics

9065SEO12

Overload Relay, Type S, melting alloy, separate mount overload, NEMA size 3, 3 pole, 3 phase, 86A, 600VAC



Main

Range of Product	S
Product destination	Starter
Thermal overload type	Melting alloy

Complementary

NEMA size	3
Number of thermal units required	3
Mounting Support	Panel
Product or Component Type	Overload relay
[Ue] rated operational voltage	600 V AC
Height	5.59 in (142.1 mm)
Width	5.31 in (134.9 mm)
Depth	5.75 in (146.1 mm)

Ordering and shipping details

Category	21661-9065 A,C,F,G,S(NOT SS)
Discount Schedule	CP1
GTIN	785901788522
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.40 in (16.256 cm)
Package 1 Width	6.70 in (17.018 cm)
Package 1 Length	8.40 in (21.336 cm)
Package 1 Weight	3.42 lb(US) (1.551 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Not compliant
China RoHS Regulation	 China RoHS Declaration

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Contractual warranty

Warranty	18 months
----------	-----------
