# 9998LH44

Contactor, Type L, multipole lighting, replacement coil, 110/120VAC 50/60Hz, 8 to 12 poles



#### Main

Wall		
Product or Component Type	Coil	
Accessory / separate part destination	Class 8903 contactor	

Complementary

[Ue] rated operational voltage	120 V AC 60 Hz	
	110 V AC 50 Hz	
Inrush power in VA	170 VA	
	180 VA	
Average consumption	35 VA	
Height	2.38 in (60.5 mm)	
Width	2.11 in (53.6 mm)	
Depth	1.46 in (37.1 mm)	

#### Ordering and shipping details

ordoning and ompping details	
Category	21756-9998 DISCOUNT CP10
Discount Schedule	CP10
GTIN	785901081289
Returnability	Yes
Country of origin	MX

## **Packing Units**

PCE	
1	
2.20 in (5.588 cm)	
2.70 in (6.858 cm)	
3.40 in (8.636 cm)	
5.76 oz (163.293 g)	
	1 2.20 in (5.588 cm) 2.70 in (6.858 cm) 3.40 in (8.636 cm)

### Offer Sustainability

EU RoHS Directive	Under investigation	
China RoHS Regulation	China RoHS Declaration	

## Contractual warranty

Warranty	18 months