

Main Range **TeSys Product or Component** Contactor coil Type Device short name LX1D6 Control circuit type AC 60 Hz [Uc] control circuit 220 V AC 60 Hz voltage 98 Ohm 68 °F (20 °C) Average resistance Inductance of closed 4.8 H circuit LC1D40 **Product Compatibility** LC1D50 LC1D65...D95

3600 cyc/h 140 °F (60 °C)

4 Mcycles

Complementary

Coil technology	Without built-in suppressor module	
Control circuit voltage limits	Drop-out: 0.30.6 Uc at 50/60 Hz (at <131 °F (55 °C)) Operational: 0.81.1 Uc at 50 Hz (at <131 °F (55 °C)) Operational: 0.851.1 Uc at 60 Hz (at <131 °F (55 °C))	
Inrush power in VA	220 VA 60 Hz cos phi 0.75 (at 68 °F (20 °C))	
Hold-in power consumption in VA	22 VA 60 Hz cos phi 0.3 (at 68 °F (20 °C))	·
Heat dissipation	610 W 50/60 Hz	·

Mechanical durability

Maximum operating rate

Environment

Ambient Air Temperature for Operation	23140 °F (-560 °C)
Net Weight	0.62 lb(US) (0.28 kg)

Ordering and shipping details

Category	22341-CONTACTOR,D,K,&F ACCESS
Discount Schedule	l12
GTIN	3389110208672
Returnability	No
Country of origin	CZ

Packing Units

PCE
1
2.24 in (5.7 cm)
3.43 in (8.7 cm)
4.92 in (12.5 cm)
10.97 oz (311.0 g)
S02
16
5.91 in (15.0 cm)
11.81 in (30.0 cm)

Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	11.77 lb(US) (5.341 kg)
Offer Sustainability	
California proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes

Contractual warranty

Contraction Warranty	
Warranty	18 months