

8910DPA73V14

Contactor, Definite Purpose, 75A, 3 pole, 40HP at 575VAC, 3 phase, 24/24VAC 50/60Hz coil, open



Main	
Product or Component Type	Definite Purpose Contactor
Line Rated Current	75 A
Number of Poles	3P
Pole contact composition	3 NO
Range of Product	DPA

Complementary

Maximum Horse Power Rating	5 Hp 115 V AC, 1 phase 15 Hp 230 V AC, 1 phase 25 Hp 230 V AC, 3 phase 40 Hp 460 V AC, 3 phase 40 hp 575 V AC, 3 phase
Locked rotor rated current	450 A 277 V AC 375 A 460 V AC 300 A 575 V AC
[Ue] rated operational voltage	600 V AC
[Uc] control circuit voltage	24 V AC 50/60 Hz
Phase	3 phase
Electrical Connection	Box lugs Quick connect terminals

Environment

Product Certifications	UL Recognized[RETURN]CSA
------------------------	--------------------------




Ordering and shipping details

Category	US1CP1B21347
Discount Schedule	CP1B
GTIN	785901118350
Returnability	No
Country of origin	CN

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.70 in (14.478 cm)
Package 1 Width	5.50 in (13.97 cm)
Package 1 Length	7.00 in (17.78 cm)
Package 1 Weight	3.68 lb(US) (1.669 kg)

Offer Sustainability

REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
RoHS exemption information	 <a href="#">Yes</a>

Contractual warranty

Warranty	18 months
----------	-----------