



Main

Range	TeSys
Device short name	ASILUF
Product or Component Type	Communication module
Product Compatibility	LUCA LUCL LUCD LUCM LUCC LUCB
Device Application	Communication
Range compatibility	TeSys TeSys Ultra LUB non reversing power base TeSys TeSys Ultra LU2B reversing power base

Complementary

Main function available	AS-Interface communication module
Mounting Mode	Plug-in
Mounting Location	Front side
Bus type	AS-Interface
Communication port protocol	Profibus DP
Addressing	31 slaves
Current consumption	200 mA 24 V output 25 mA normal operation 30 mA fault operation
Switching current capacity	500 mA 24 V against short-circuits solid state
Local signalling	2 LEDs front panel
Connection pitch	0.15 in (3.81 mm) output 0.20 in (5.08 mm) input
Connections - terminals	Input screw clamp terminals 1 0.00...0.00 in ² (0.2...1.5 mm ²)flexible without cable end Input screw clamp terminals 1 0.00...0.00 in ² (0.2...1.5 mm ²)rigid without cable end Input screw clamp terminals 1 0.00...0.00 in ² (0.25...1.5 mm ²)flexible with cable end Input screw clamp terminals 2 0.00...0.00 in ² (0.2...1 mm ²)flexible without cable end Input screw clamp terminals 2 0.00...0.00 in ² (0.2...1 mm ²)rigid without cable end Input screw clamp terminals 2 0.00...0.00 in ² (0.25...1 mm ²)flexible with cable end Input screw clamp terminals 2 0.00...0.00 in ² (0.5...1 mm ²)flexible with cable end Output screw clamp terminals 1 0.00...0.00 in ² (0.14...1 mm ²)flexible without cable end Output screw clamp terminals 1 0.00...0.00 in ² (0.14...1 mm ²)rigid without cable end Output screw clamp terminals 1 0.00...0.00 in ² (0.25...0.5 mm ²)flexible with cable end Output screw clamp terminals 1 0.00...0.00 in ² (0.25...1 mm ²)flexible with cable end Output screw clamp terminals 2 0.00...0.00 in ² (0.14...0.5 mm ²)rigid without cable end Output screw clamp terminals 2 0.00...0.00 in ² (0.14...0.75 mm ²)flexible without cable end Output screw clamp terminals 2 0.00...0.00 in ² (0.25...0.34 mm ²)flexible with cable end Output screw clamp terminals 2 0.00 in ² (0.5 mm ²)flexible with cable end
Tightening torque	Input 4.43...5.31 lbf.in (0.5...0.6 N.m) 0.14 in (3.5 mm) Output 1.77...2.21 lbf.in (0.2...0.25 N.m) 0.10 in (2.5 mm)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

IP degree of protection	IP20 conforming to IEC 60529
-------------------------	------------------------------

Ordering and shipping details

Category	22398-TESYS U - MULTI-FCTN CTRL MOD(LUCM)
Discount Schedule	I11
GTIN	3389110365801
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.34 in (3.4 cm)
Package 1 Width	1.93 in (4.9 cm)
Package 1 Length	3.70 in (9.4 cm)
Package 1 Weight	2.15 oz (61.0 g)
Unit Type of Package 2	S01
Number of Units in Package 2	20
Package 2 Height	5.91 in (15.0 cm)
Package 2 Width	5.91 in (15.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	3.12 lb(US) (1.415 kg)

Offer Sustainability

California proposition 65	WARNING: Cancer - www.P65Warnings.ca.gov
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 China RoHS Declaration
RoHS exemption information	 Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------