### HMIG3U

## base unit, Harmony GTU, premium box, 1GB SD card





## Main

| · · · · · · · · · · · · · · · · · · · |                        |
|---------------------------------------|------------------------|
| Range of Product                      | Harmony GTU            |
| Product or Component<br>Type          | Base unit              |
| Device short name                     | Premium Box            |
| Range Compatibility                   | Harmony GTU            |
| [Us] rated supply voltage             | 1224 V DC power supply |
|                                       |                        |

#### Complementary

| Integrated connection type  | Ethernet TCP/IP 2 RJ45                                      |
|-----------------------------|---|
|                             | COM1 serial link RJ45 RS485 110115200 bit/s                 |
|                             | COM1 serial link RJ45 RS485 187.5 kbit/s                    |
|                             | COM2 serial link SUB-D 9 RS232C/RS422/RS485 110115200 bit/s |
|                             | COM2 serial link SUB-D 9 RS232C/RS422/RS485 187.5 kbit/s    |
|                             | Auxiliary port terminal block                               |
|                             | Expansion unit fieldbus card                                |
|                             | USB 2.0 port 2 USB type A                                   |
|                             | USB 2.0 port mini B USB                                     |
| Communication port protocol | Modbus  |
|                             | Modbus TCP/IP   |
|                             | Uni-Telway  |
| Operating system            | Harmony   |
| Software package            | Vijeo Designer run time                                     |
| Processor name              | CPU RISC 600 MHz  |
| Data storage equipment      | 1 GB SD card  |
| Port Ethernet               | 10BASE-T/100BASE-TX/1000BASE-T                              |
| Memory description          | 256 MB RAM internal 2 x 13 mm board)                        |
|                             | 512 KB NVRAM backup memory                                  |
| Type of cooling             | Natural convection  |
| Width                       | 7.40 in (188 mm)  |
| Height                      | 5.16 in (131 mm)  |
| Depth                       | 1.77 in (45 mm)   |
| Net Weight                  | 1.98 lb(US) (0.9 kg)  |

#### Environment

| Standards                             | CSA C22.2 No 142  |
|---------------------------------------|---|
|                                       | *********   |
|                                       | ANSI/ISA 12-12-01<br>UL 508                                   |
|                                       | Class I division 2 CSA C22.2 No 213                           |
|                                       | IEC 61132-2   |
| Product certifications                | CE[RETURN]CULus[RETURN]ATEX[RETURN]IEC-                       |
|                                       | Ex[RETURN]RCM[RETURN]GL[RETURN]KC[RETURN]CUL[RETURN]EAC[RETUR |
| Ambient air temperature for operation | 32140 °F (060 °C)   |
| Ambient air temperature for storage   | -4140 °F (-2060 °C)   |
| Pollution degree                      | 2 IEC 61131-2 ed.3  |
| Relative Humidity                     | 1090 % non-condensing   |
| Operating altitude                    | 6561.68 ft (2000 m)   |
|                                       |   |

| Vibration resistance          | 3.5 mm constant amplitude 59 Hz) IEC 61131-2<br>9.8 m/s² 9150 Hz) IEC 61131-2   |
|-------------------------------|---|
| Electromagnetic compatibility | Electrostatic discharge immunity test level 3 conforming to IEC 61000-4-2   |
| Ordering and shipping details |   |
| Category                      | 22567-MAGELIS HMI GTU   |
| Discount Schedule             | MC2   |
| GTIN                          | 3606480687204   |
| Returnability                 | Yes   |
| Country of origin             | CN  |
| ocana, or ongin               |   |
| Packing Units                 |   |
| Unit Type of Package 1        | PCE   |
| Number of Units in Package 1  | 1   |
| Package 1 Height              | 5.62 in (14.267 cm)   |
| Package 1 Width               | 8.44 in (21.441 cm)   |
| Package 1 Length              | 10.43 in (26.48 cm)   |
| Package 1 Weight              | 2.78 lb(US) (1.26 kg)   |
| Unit Type of Package 2        | S04   |
| Number of Units in Package 2  | 4   |
| Package 2 Height              | 11.81 in (30 cm)  |
| Package 2 Width               | 15.75 in (40 cm)  |
| Package 2 Length              | 23.62 in (60 cm)  |
| Package 2 Weight              | 203.25 oz (5762 g)  |
| Unit Type of Package 3        | P12   |
| Number of Units in Package 3  | 48  |
| Package 3 Height              | 37.40 in (95 cm)  |
| Package 3 Width               | 31.50 in (80 cm)  |
| Package 3 Length              | 47.24 in (120 cm)   |
| Package 3 Weight              | 2756.40 oz (78144 g)  |
|                               |   |
| Offer Sustainability          | Coron Describes anadost   |
| Sustainable offer status      | Green Premium product   |
| California proposition 65     | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACh Regulation              | ☑ REACh Declaration   |
| EU RoHS Directive             | Pro-active compliance (Product out of EU RoHS legal scope)  |
| Mercury free                  | Yes   |
| China RoHS Regulation         | China RoHS Declaration  |
| RoHS exemption information    | ₫Yes  |
| Environmental Disclosure      | Product Environmental Profile   |
| Circularity Profile           | <sup>™</sup> End Of Life Information  |
| WEEE                          | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.  |

Life Is On Schneider

18 months

Warranty

Contractual warranty


# Product data sheet Dimensions Drawings

## HMIG3U

#### **Dimensions**

#### **External Dimensions**

in. (3)



- 1 Front
- 2 Left
- 3 Bottom