VX5VPS4001

Wear part, enclosure door, fan for variable speed drive, Altivar 340, Altivar Process 600 900, from 15 to 45kW



Main

Range Compatibility	Altivar 340 Altivar Process 600/900
Accessory / separate part type	Fan kit
Accessory / separate part category	Cooling accessory
Product or Component Type	Fan

Complementary

Kit composition	Fan
	Mounting bracket
	Instruction sheet
Product compatibility	Variable speed drive ATV630 wall mount 15 kW 200240 V
	Variable speed drive ATV630 wall mount 18 kW 200240 V
	Variable speed drive ATV630 wall mount 22 kW 200240 V
	Variable speed drive ATV630 wall mount 30 kW 380480 V
	Variable speed drive ATV630 wall mount 37 kW 380480 V
	Variable speed drive ATV630 wall mount 45 kW 380480 V
	Variable speed drive ATV930 wall mount 15 kW 200240 V
	Variable speed drive ATV930 wall mount 18 kW 200240 V
	Variable speed drive ATV930 wall mount 22 kW 200240 V
	Variable speed drive ATV930 wall mount 30 kW 380480 V
	Variable speed drive ATV930 wall mount 37 kW 380480 V
	Variable speed drive ATV930 wall mount 45 kW 380480 V
	Variable speed drive ATV340 30 kW 380480 V
	Variable speed drive ATV340 37 kW 380480 V

Ordering and shipping details

Category	22205-ATV630 FRAMES 1 & 2
Discount Schedule	CP4E
GTIN	3606480716119
Returnability	Yes
Country of origin	CN

Packing Units

racking units	
Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	2.80 in (7.100 cm)
Package 1 Width	6.81 in (17.300 cm)
Package 1 Length	9.25 in (23.500 cm)
Package 1 Weight	20.60 oz (584.000 g)
Unit Type of Package 2	S03
Number of Units in Package 2	6
Package 2 Height	11.81 in (30.000 cm)
Package 2 Width	11.81 in (30.000 cm)
Package 2 Length	15.75 in (40.000 cm)
Package 2 Weight	8.88 lb(US) (4.030 kg)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein.
This documentation is not intended as a substitute for and is not to be used for determining suitability of these products for specific user applications.
It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₽

Contractual warranty

Warranty	18 months