

Product data sheet

Characteristics

1006737B

Meter socket, ringless, 2 gang, 1 phase, 3 wire, 200A, 4 jaws, 600VAC max, no bypass, no jaw release



Main

Product Type	Meter Socket
Rated Current	200 A
Number of Meter Sockets	2
Number of Phases	1 phase
Rated Operational Voltage	600 V AC

Complementary

Number of Jaws	4 without jaw release
Bypass Type	No bypass
Meter Socket Type	Ringless
Certifications	UL Listed
Enclosure Rating	NEMA 3R
Wire Gauge	AWG 8...250 kcmil (aluminium/copper) branch lugs 350 kcmil (aluminium/copper) main lugs
Service Feed Location	UG
Wiring Configuration	3-wire
Hub Type	Solid top

Ordering and shipping details

Category	00039-METER SOCKETS & HUBS
Discount Schedule	DE4
GTIN	785901632801
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.30 in (16.002 cm)
Package 1 Width	14.90 in (37.846 cm)
Package 1 Length	24.80 in (62.992 cm)
Package 1 Weight	28.00 lb(US) (12.701 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Nickel (Metallic), which is known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Under investigation

Contractual warranty

Warranty

18 months
