



Main

Product Range	Type S
Component type	Push-button
Used with	Contactor starter

Complementary

NEMA size	2 0 6 4 5 3 7 00 1
Marking	START-STOP ON-OFF
Mounting Mode	Panel-mounted
Rated breaking capacity	6 A 120 V AC inductive control circuit UL 508 3 A 240 V AC inductive control circuit UL 508 1.2 A 600 V AC inductive control circuit UL 508 10 A 600 V AC resistive control circuit UL 508 1.1 A 125 V DC resistive control circuit UL 508 0.55 A 250 V DC resistive control circuit UL 508 0.2 A 600 V DC resistive control circuit UL 508

Environment

NEMA Degree of Protection	NEMA 1 NEMA 12/3R
Product Certifications	UL Recognized[RETURN]CSA

Ordering and shipping details

Category	21761-9999 DISCOUNT CP1
Discount Schedule	CP1
GTIN	785901030171
Returnability	Yes
Country of origin	MX

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.39 in (8.6 cm)
Package 1 Width	4.41 in (11.2 cm)
Package 1 Length	6.50 in (16.5 cm)
Package 1 Weight	16.48 oz (467.2 g)

Offer Sustainability

California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov
EU RoHS Directive	Under investigation
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------