Product data sheet

Specifications



Wear part, enclosure door, fan for variable speed drive, Altivar 340, Altivar Process 600 900, from 15 to 45kW

VX5VPS4001

Main

Range compatibility	Altivar 340 Altivar Process 600/900
Accessory / separate part type	Fan kit
Accessory / separate part category	Cooling accessory
Product or component type	Fan

Complementary

Kit composition	Fan Mounting bracket Instruction sheet
Product compatibility	Variable speed drive ATV630 wall mount 15 kW 200240 V Variable speed drive ATV630 wall mount 18 kW 200240 V Variable speed drive ATV630 wall mount 22 kW 200240 V Variable speed drive ATV630 wall mount 30 kW 380480 V Variable speed drive ATV630 wall mount 37 kW 380480 V Variable speed drive ATV630 wall mount 45 kW 380480 V Variable speed drive ATV930 wall mount 15 kW 200240 V Variable speed drive ATV930 wall mount 18 kW 200240 V Variable speed drive ATV930 wall mount 22 kW 200240 V Variable speed drive ATV930 wall mount 30 kW 380480 V Variable speed drive ATV930 wall mount 37 kW 380480 V Variable speed drive ATV930 wall mount 45 kW 380480 V Variable speed drive ATV930 wall mount 45 kW 380480 V Variable speed drive ATV340 30 kW 380480 V Variable speed drive ATV340 37 kW 380480 V

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	7.1 cm
Package 1 Width	17.3 cm
Package 1 Length	23.5 cm
Package 1 Weight	584.0 g
Unit Type of Package 2	S03
Number of Units in Package 2	6
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	4.18 kg

Offer Sustainability

REACh Regulation	REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
China RoHS Regulation	China RoHS declaration
RoHS exemption information	Yes
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Contractual warranty	
Warranty	18 months

Recommended replacement(s)