# 8502SFO2V03

NEMA Contactor, Type S, nonreversing, Size 4, 135A, 100 HP at 575 VAC, 3 phase, up to 100 kA, 3 pole, 240 VAC coil, open



#### Main

Product Type	Contactor
Product Range	8502S
Contactor Type	Non-reversing

Complementary

4	
135 A	
3P	
600 V AC	
3 phase	
40 HP 200 V AC 50 HP 230 V AC 100 HP 460 V AC 100 HP 575 V AC	
Circuit-breaker 225 A maximum, SCCR: 100 kA at 480 V AC Fuse J 200 A maximum, SCCR: 100 kA at 600 V AC Fuse T 200 A maximum, SCCR: 100 kA at 600 V AC Fuse RK1 200 A maximum, SCCR: 100 kA at 600 V AC Fuse RK5 200 A maximum, SCCR: 100 kA at 600 V AC	
240 V AC 60 Hz 220 V AC 50 Hz	
Common control circuit	
No control units	
No indicator	
Without	
Fuse not supplied	
Screw clamp terminals	
8.19 in (208.03 mm)	
6.00 in (152.40 mm)	
6.50 in (165.10 mm)	
	135 A 3P 600 V AC 3 phase 40 HP 200 V AC 50 HP 230 V AC 100 HP 460 V AC 100 HP 575 V AC  Circuit-breaker 225 A maximum, SCCR: 100 kA at 480 V AC Fuse J 200 A maximum, SCCR: 100 kA at 600 V AC Fuse T 200 A maximum, SCCR: 100 kA at 600 V AC Fuse RK1 200 A maximum, SCCR: 100 kA at 600 V AC Fuse RK5 200 A maximum, SCCR: 100 kA at 600 V AC Fuse RK5 200 A maximum, SCCR: 100 kA at 600 V AC Common control circuit No control units No indicator Without Fuse not supplied Screw clamp terminals 8.19 in (208.03 mm) 6.00 in (152.40 mm)

#### Environmental

Enclosure Type	Not rated (open device)
Certifications	UL listed file E78351 CCN NLDX[RETURN]CSA

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherent for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the dourn and restring of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Ordering and shipping details

Category	21193-8502,36 SE,SF(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	785901830801
Returnability	No
Country of origin	MX

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	8.19 in (20.8 cm)
Package 1 Width	5.98 in (15.2 cm)
Package 1 Length	6.50 in (16.5 cm)
Package 1 Weight	18.02 lb(US) (8.174 kg)

# Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration

### Contractual warranty

Warranty	18 months