



TYPE APPROVAL CERTIFICATE

Certificate No:
TAA00002ZS
Revision No:
1

This is to certify:

That the Electromechanical Relays

with type designation(s)

RXG (Relays), RGZE (Sockets)

Issued to

Schneider Electric Asia Pte Ltd
Singapore, Singapore

is found to comply with

DNV rules for classification – Ships, offshore units, and high speed and light craft

Application :

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV.

| Type | Temperature | Humidity | Vibration | EMC | Enclosure |
|-----------------------|-------------|----------|-----------|----------|----------------|
| RXG (Relays) | B | B | A | A | IP20 *) |
| RGZE (Sockets) | B | B | A | A | IP20 *) |

Issued at **Hamburg** on **2023-10-04**

for **DNV**

This Certificate is valid until **2026-05-25**.

DNV local unit: **Certification of Materials - Singapore**

Approval Engineer: **Didier Girardin**

.....
Joannis Papanuskas
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid.
The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Form code: TA 251

Revision: 2022-12

www.dnv.com

Page 1 of 5

Product description

Electromechanical relays with different sockets:

| | | | |
|-----------|-----|-----------------|-------------------------------------|
| RGZE1S35M | 1CO | screw connector | socket with clamp, separate contact |
| RGZE1S48M | 2CO | screw connector | socket with clamp, separate contact |
| RGZE05P | 1CO | push-in | socket with clamp, separate contact |
| RGZE08P | 2CO | push-in | socket with clamp, separate contact |

Description:

Cover: Clear: Clear cover, blank: Front cover

Lockable test button: +LTB: Yes, -LTB: No

LED: +LED: Yes, blank: No

| Type | Poles | Current | Description | Voltage |
|---------|-------|---------|---------------|---------|
| RXG15B7 | 1CO | 10A | Relay, Clear | 24VAC |
| RXG15E7 | 1CO | 10A | Relay, Clear | 48VAC |
| RXG15F7 | 1CO | 10A | Relay, Clear | 120VAC |
| RXG15M7 | 1CO | 10A | Relay, Clear | 220VAC |
| RXG15P7 | 1CO | 10A | Relay, Clear | 230VAC |
| RXG15RD | 1CO | 10A | Relay, Clear | 6VDC |
| RXG15JD | 1CO | 10A | Relay, Clear | 12VDC |
| RXG15BD | 1CO | 10A | Relay, Clear | 24VDC |
| RXG15ED | 1CO | 10A | Relay, Clear | 48VDC |
| RXG15ND | 1CO | 10A | Relay, Clear | 60VDC |
| RXG15FD | 1CO | 10A | Relay, Clear | 110VDC |
| RXG13B7 | 1CO | 10A | Relay-LTB+LED | 24VAC |
| RXG13E7 | 1CO | 10A | Relay-LTB+LED | 48VAC |
| RXG13F7 | 1CO | 10A | Relay-LTB+LED | 120VAC |
| RXG13M7 | 1CO | 10A | Relay-LTB+LED | 220VAC |
| RXG13P7 | 1CO | 10A | Relay-LTB+LED | 230VAC |
| RXG13RD | 1CO | 10A | Relay-LTB+LED | 6VDC |
| RXG13JD | 1CO | 10A | Relay-LTB+LED | 12VDC |
| RXG13BD | 1CO | 10A | Relay-LTB+LED | 24VDC |
| RXG13ED | 1CO | 10A | Relay-LTB+LED | 48VDC |
| RXG13ND | 1CO | 10A | Relay-LTB+LED | 60VDC |
| RXG13FD | 1CO | 10A | Relay-LTB+LED | 110VDC |
| RXG11B7 | 1CO | 10A | Relay+LTB-LED | 24VAC |
| RXG11E7 | 1CO | 10A | Relay+LTB-LED | 48VAC |
| RXG11F7 | 1CO | 10A | Relay+LTB-LED | 120VAC |
| RXG11M7 | 1CO | 10A | Relay+LTB-LED | 220VAC |
| RXG11P7 | 1CO | 10A | Relay+LTB-LED | 230VAC |
| RXG11RD | 1CO | 10A | Relay+LTB-LED | 6VDC |
| RXG11JD | 1CO | 10A | Relay+LTB-LED | 12VDC |
| RXG11BD | 1CO | 10A | Relay+LTB-LED | 24VDC |
| RXG11ED | 1CO | 10A | Relay+LTB-LED | 48VDC |
| RXG11ND | 1CO | 10A | Relay+LTB-LED | 60VDC |
| RXG11FD | 1CO | 10A | Relay+LTB-LED | 110VDC |
| RXG12B7 | 1CO | 10A | Relay+LTB+LED | 24VAC |
| RXG12E7 | 1CO | 10A | Relay+LTB+LED | 48VAC |
| RXG12F7 | 1CO | 10A | Relay+LTB+LED | 120VAC |
| RXG12M7 | 1CO | 10A | Relay+LTB+LED | 220VAC |
| RXG12P7 | 1CO | 10A | Relay+LTB+LED | 230VAC |
| RXG12RD | 1CO | 10A | Relay+LTB+LED | 6VDC |
| RXG12JD | 1CO | 10A | Relay+LTB+LED | 12VDC |
| RXG12BD | 1CO | 10A | Relay+LTB+LED | 24VDC |
| RXG12ED | 1CO | 10A | Relay+LTB+LED | 48VDC |
| RXG12ND | 1CO | 10A | Relay+LTB+LED | 60VDC |
| RXG12FD | 1CO | 10A | Relay+LTB+LED | 110VDC |

| Type | Poles | Current | Description | Voltage |
|---------|-------|---------|---------------|---------|
| RXG25B7 | 2CO | 5A | Relay, Clear | 24VAC |
| RXG25E7 | 2CO | 5A | Relay, Clear | 48VAC |
| RXG25F7 | 2CO | 5A | Relay, Clear | 120VAC |
| RXG25M7 | 2CO | 5A | Relay, Clear | 220VAC |
| RXG25P7 | 2CO | 5A | Relay, Clear | 230VAC |
| RXG25RD | 2CO | 5A | Relay, Clear | 6VDC |
| RXG25JD | 2CO | 5A | Relay, Clear | 12VDC |
| RXG25BD | 2CO | 5A | Relay, Clear | 24VDC |
| RXG25ED | 2CO | 5A | Relay, Clear | 48VDC |
| RXG25ND | 2CO | 5A | Relay, Clear | 60VDC |
| RXG25FD | 2CO | 5A | Relay, Clear | 110VDC |
| RXG23B7 | 2CO | 5A | Relay-LTB+LED | 24VAC |
| RXG23E7 | 2CO | 5A | Relay-LTB+LED | 48VAC |
| RXG23F7 | 2CO | 5A | Relay-LTB+LED | 120VAC |
| RXG23M7 | 2CO | 5A | Relay-LTB+LED | 220VAC |
| RXG23P7 | 2CO | 5A | Relay-LTB+LED | 230VAC |
| RXG23RD | 2CO | 5A | Relay-LTB+LED | 6VDC |
| RXG23JD | 2CO | 5A | Relay-LTB+LED | 12VDC |
| RXG23BD | 2CO | 5A | Relay-LTB+LED | 24VDC |
| RXG23ED | 2CO | 5A | Relay-LTB+LED | 48VDC |
| RXG23ND | 2CO | 5A | Relay-LTB+LED | 60VDC |
| RXG23FD | 2CO | 5A | Relay-LTB+LED | 110VDC |
| RXG21B7 | 2CO | 5A | Relay+LTB-LED | 24VAC |
| RXG21E7 | 2CO | 5A | Relay+LTB-LED | 48VAC |
| RXG21F7 | 2CO | 5A | Relay+LTB-LED | 120VAC |
| RXG21M7 | 2CO | 5A | Relay+LTB-LED | 220VAC |
| RXG21P7 | 2CO | 5A | Relay+LTB-LED | 230VAC |
| RXG21RD | 2CO | 5A | Relay+LTB-LED | 6VDC |
| RXG21JD | 2CO | 5A | Relay+LTB-LED | 12VDC |
| RXG21BD | 2CO | 5A | Relay+LTB-LED | 24VDC |
| RXG21ED | 2CO | 5A | Relay+LTB-LED | 48VDC |
| RXG21ND | 2CO | 5A | Relay+LTB-LED | 60VDC |
| RXG21FD | 2CO | 5A | Relay+LTB-LED | 110VDC |
| RXG22B7 | 2CO | 5A | Relay+LTB+LED | 24VAC |
| RXG22E7 | 2CO | 5A | Relay+LTB+LED | 48VAC |
| RXG22F7 | 2CO | 5A | Relay+LTB+LED | 120VAC |
| RXG22M7 | 2CO | 5A | Relay+LTB+LED | 220VAC |
| RXG22P7 | 2CO | 5A | Relay+LTB+LED | 230VAC |
| RXG22RD | 2CO | 5A | Relay+LTB+LED | 6VDC |
| RXG22JD | 2CO | 5A | Relay+LTB+LED | 12VDC |
| RXG22BD | 2CO | 5A | Relay+LTB+LED | 24VDC |
| RXG22ED | 2CO | 5A | Relay+LTB+LED | 48VDC |
| RXG22ND | 2CO | 5A | Relay+LTB+LED | 60VDC |
| RXG22FD | 2CO | 5A | Relay+LTB+LED | 110VDC |

Manufacturing Place

[REDACTED]

[REDACTED]

Application/Limitation

The Type Approval covers hardware listed under Product description. When the hardware is used in applications to be classed by DNV GL, documentation for the actual application is to be submitted for approval by the manufacturer of the application system in each case. Reference is made to DNV GL rules for classification of ships Pt.4 Ch.9 Control and monitoring systems.

Type Approval documentation

See ANNEX

Tests carried out

Applicable tests according to class guideline DNV-CG-0339, August 2021

Marking of product

The products to be marked with

- manufacturer name
- model name
- serial number

Periodical assessment

The scope of the periodical assessment is to verify that the conditions stipulated for the type are complied with, and that no alterations are made to the product design or choice of systems, software versions, components and/or materials.

The main elements of the assessment are:

- Ensure that type approved documentation is available
- Inspection of factory samples, selected at random from the production line (where practicable)
- Review of production and inspection routines, including test records from product sample tests and control routines
- Ensuring that systems, software versions, components and/or materials used comply with type approved documents and/or referenced system, software, component and material specifications
- Review of possible changes in design of systems, software versions, components, materials and/or performance, and make sure that such changes do not affect the type approval given
- Ensuring traceability between manufacturer's product type marking and the type approval certificate

Periodical assessment is to be performed after 2 years and after 3.5 years. A renewal assessment will be performed at renewal of the certificate.

END OF CERTIFICATE



Job Id: 262.1-039658-1
Certificate No: TAA00002ZS
Revision No: 1

Type Approval documentation

(hidden)

| Title | Drw No | Rev |
|---|-------------|-----|
| Product Identification Relays | | |
| Product References | | |
| Product Identification Socket | | |
| Product Test Plan Summary | | |
| Product Test Plan | | |
| Contact Resistance | EAV9457007 | 00 |
| Electrical Endurance - D | EAV9457009- | 02 |
| Release Value | EAV9457017 | 01 |
| Release_Bounce Time | EAV9457005 | 00 |
| Operate Value | EAV9457016 | 01 |
| Electrical Endurance | EAV9457008- | 02 |
| Operate_Bounce Time | EAV9457004 | 00 |
| Mechanical Endurance | EAV9457001 | 02 |
| Heating | EAV9457011 | 01 |
| Dry Heat Test Report | | |
| Enclosure (IP20) Test Report | | |
| Inclination Test Report | | |
| Insulation Resistance Test Report | | |
| Electrical Power Supply Failure Test Report | | |
| Cold Test Report | | |
| High Voltage Test Report | | |
| Damp Heat Test Report | | |
| Power Supplies Variation Test Report | | |
| Vibration Test Report (attachment) | | |
| Vibration Test Report | | |
| Flammability Material Declaration | | |