## Product data sheet Characteristics

# 8702SFO3V02S

NEMA Contactor, Type S, reversing, horizontal, Size 4, 135A, 100HP at 575VAC, 3 phase, up to 100kA, 3 pole, 120VAC coil, open style



#### Main

Product Type	Contactor
Product Range	Type S
Contactor Type	Reversing

Complementary

Complementary		
NEMA Size	4	
Rated Current	135 A	
Number of Poles	3P	
Mounting Orientation	Horizontal	
Wiring Mode	3 wires	
Maximum Voltage Rating	600 V AC	
Phase	3 phase	
Horsepower Rating	40 HP 200 V AC 50 HP 230 V AC 100 HP 460 V AC 100 HP 575 V AC	
SCCR	Circuit-breaker 225 A maximum, SCCR: 100 kA at 480 V AC Fuse J 200 A maximum, SCCR: 100 kA at 600 V AC Fuse T 200 A maximum, SCCR: 100 kA at 600 V AC Fuse RK1 200 A maximum, SCCR: 100 kA at 600 V AC Fuse RK5 200 A maximum, SCCR: 100 kA at 600 V AC	
Coil Voltage	110 V AC 50 Hz 120 V AC 60 Hz	
Control Circuit Type	Separate control circuit	
Control Units	No control units	
Pilot Light	No indicator	
Other Equipment	Fuse not supplied	
Terminal Type	Screw clamp terminals	
Height	11.69 in (296.93 mm)	
Width	14.25 in (361.95 mm)	
Depth	7.00 in (177.8 mm)	

#### Environment

Enclosure Type	Not rated (open device)
Certifications	UL Listed[RETURN]CSA

### Ordering and shipping details

Category	21273-8702,36 SE,SF(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	785901841319
Returnability	No
Country of origin	MX

#### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	11.69 in (29.7 cm)
Package 1 Width	14.25 in (36.2 cm)
Package 1 Length	7.01 in (17.8 cm)
Package 1 Weight	44.00 lb(US) (19.958 kg)

### Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration

#### Contractual warranty

144	10 11
Warrantv	18 months
Trairainty	To monute