# 9001SKS11FBH13

Selector switch, Harmony 9001SK, plastic, long handle, black, 30mm, 2 positions, stay put, 1 C/O





### Main

Range of Product	ct Harmony 9001SK	
Product or Component Type	Selector switch	
Device short name	9001SK	
Type of operator Stay put		
Operator profile	Black long handle	

Complementary

Plastic	
1.18 in (30 mm)	
2 positions	
1 C/O	
9001KA1 side 1 or 2	
Complete product	
Black	
Long handle	
Stay put	
30 mm	
5	
	1.18 in (30 mm) 2 positions 1 C/O 9001KA1 side 1 or 2 Complete product Black Long handle Stay put 30 mm

#### Environment

Protective treatment	TC
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)
Ambient Air Temperature for Operation	-13158 °F (-2570 °C)
Electrical shock protection class	Class II IEC 61140
IP degree of protection	IP66 IEC 60529
NEMA degree of protection	NEMA 1/2/3/3R/4/4X/6/12/13
Product Certifications	UL listed file E42259 CCN NKCR[RETURN]CSA LR24590 class 3211 03[RETURN]CE

### Ordering and shipping details

Category	21429-9001 SK,SKY
Discount Schedule	CS1
GTIN	785901043591
Returnability	No
Country of origin	MX

# Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.08 in (12.903 cm)
Package 1 Width	2.00 in (5.08 cm)
Package 1 Length	12.90 in (32.774 cm)
Package 1 Weight	3.20 oz (90.719 g)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EPEU RoHS  Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	☐ China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

## Contractual warranty

Warranty	18 months