Product data sheet Characteristics

S33170

Circuit breaker accessory, PowerPacT P, cradle postion switch, 1a/1b form C, connected/ test/disconnect



Main

IVICIII		
Range of Product	PowerPact P MasterPact NT MasterPact NW	
Product or Component Type	Switch	

Complementary

Rated voltage	240690 V AC 24250 V DC
Trip unit protection functions	Basic protection

Environment

Product Certifications	UL Listed[RETURN]CSA
Product Certifications	UL LISTED[RETURN]CSA

Ordering and shipping details

01290-MASTERPACT ACCESSORIES
DE2F
785901828402
Yes
US

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	1.00 in (2.54 cm)	
Package 1 Width	4.50 in (11.43 cm)	
Package 1 Length	5.00 in (12.7 cm)	
Package 1 Weight	1.60 oz (45.359 g)	

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is	
- Commontant proposition of	known to the State of California to cause cancer, and DIDP, which is known to	
	the State of California to cause birth defects or other reproductive harm. For more	
	information go to www.P65Warnings.ca.gov	
FILD-HO Diverti		
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS	
	Declaration	
Toxic heavy metal free	Yes	
Mercury free	Yes	
China RoHS Regulation	☑ China RoHS Declaration	
	Cnina Rons Declaration	
RoHS exemption information	₫Yes	
	165	

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or intellability of these products for specific user applications. It is the douwn part is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Warranty 18 months