112T3HNV

Low voltage transformer, non ventilated dry type, 3 phase, 112.5kVA, 480V primary, 208Y/120V secondary, Type 3R





Main

Product	Non-Ventilated Transformer
Enclosure Code	24E
Insulation Temperature	428 °F (220 °C)
Phase	3 phase
Primary Voltage	480 V delta
Power Rating	112.5 kVA
Secondary Voltage	208Y/120 V
Full Capacity Taps	6 2.5 % 2+ 4-
Temperature Rise	150 °C
Winding Material	Aluminium

Ordering and shipping details

Category	16273-NON VENT NON RESIN LVGP
Discount Schedule	PE2
GTIN	785901340270
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	52.99 in (134.6 cm)	
Package 1 Width	29.49 in (74.9 cm)	
Package 1 Length	35.98 in (91.4 cm)	
Package 1 Weight	1280.00 lb(US) (580.598 kg)	

Offer Sustainability

Sustainable offer status	Green Premium product	
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl Glycidyl Ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	☐ REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant	
Toxic heavy metal free	Yes	
Mercury free	Yes	
China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	₫Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	

Contractual warranty

Warranty	18 months
----------	-----------