# 8502SCO2V02S

NEMA Contactor, Type S, nonreversing, Size 1, 27A, 10 HP at 575 VAC, 3 phase, up to 100 kA, 3 pole, 120 VAC coil, open



#### Main

Product Type	Contactor
Product Range	8502S
Contactor Type	Non-reversing

Complementary

Complementary		
NEMA Size	1	
Rated Current	27 A	
Number of Poles	3P	
Maximum Voltage Rating	600 V AC	
Phase	3 phase	
Horsepower Rating	7.5 HP 200 V AC 7.5 HP 230 V AC 10 HP 460 V AC 10 HP 575 V AC	
SCCR	Circuit-breaker 70 A maximum, SCCR: 100 kA at 480 V AC Fuse J 60 A maximum, SCCR: 100 kA at 600 V AC Fuse T 60 A maximum, SCCR: 100 kA at 600 V AC Fuse RK1 60 A maximum, SCCR: 100 kA at 600 V AC Fuse RK5 60 A maximum, SCCR: 100 kA at 600 V AC	
Coil Voltage	120 V AC 60 Hz 110 V AC 50 Hz	
Control Circuit Type	Separate control circuit	
Control Units	No control units	
Pilot Light	No indicator	
Auxiliary Contacts	Without	
Other Equipment	Fuse not supplied	
Terminal Type	Screw clamp terminals	
Height	4.34 in (110.24 mm)	
Width	3.22 in (81.79 mm)	
Depth	4.22 in (107.19 mm)	

### Environmental

Enclosure Type	Not rated (open device)
Certifications	UL listed file E78351 CCN NLDX[RETURN]CSA

## Ordering and shipping details

Category	21192-8502,36 SC,SD(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	785901862901
Returnability	Yes
Country of origin	MX

### Packing Units

3		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	4.50 in (11.43 cm)	
Package 1 Width	5.80 in (14.732 cm)	
Package 1 Length	8.00 in (20.32 cm)	
Package 1 Weight	3.30 lb(US) (1.497 kg)	

# Offer Sustainability

ulifornia proposition 65  WARNING: This product can expose you to chemicals including: Lead compounds, which is known to the State of California to cause of and birth defects or other reproductive harm. For more information gwww.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	☑ China RoHS Declaration

### Contractual warranty

	The state of the s
Warranty	18 months
vvarianty	16 months