8536SHO2V02S

NEMA Motor Starter, Type S, nonreversing, Size 6, 540A, 400 HP at 460 VAC, 3 phase, 3 pole, melting alloy, 120 VAC coil, open



Main

Product Type	Motor starter	
Product Range	S	
Starter Type	Non reversing	

Complementary

Complementary		
NEMA Size	6	
Rated Current	540 A	
Number of Poles	3P	
Maximum Voltage Rating	600 V AC	
Phase	3 phase	
Type of Overload	Melting alloy 3	
Horsepower Rating	150 HP 200 V AC 200 HP 230 V AC 400 HP 460 V AC 400 HP 575 V AC	
Coil Voltage	110 V AC 50 Hz 120 V AC 60 Hz	
Control Circuit Type	Control circuit transformer	
Control Units	No control units	
Pilot Light	Without pilot light	
Auxiliary Contacts	Without	
Other Equipment	2 fuses (primary), 2 fuses (secondary)	
Terminal Type	Screw clamp terminals	
Height	28.06 in (712.72 mm)	
Width	12.34 in (313.44 mm)	
Depth	9.00 in (228.60 mm)	

Environment

Enclosure Type	Not rated (open device)	
Certifications	UL Listed[RETURN]CSA[RETURN]NEMA	

Ordering and shipping details

21195-8502,36 SH,SJ(NOT S*R,T,W)	
CP1	
785901625674	
Yes	
MX	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	28.07 in (71.3 cm)	
Package 1 Width	12.32 in (31.3 cm)	
Package 1 Length	9.02 in (22.9 cm)	
Package 1 Weight	117.00 lb(US) (53.07 kg)	

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Not compliant	
China RoHS Regulation	China RoHS Declaration	

Contractual warranty

Warranty	18 months	
vvarrarity	TO MONUS	