NSYEBCD25622

Power distribution block, Linergy, enclosed, 510A CU, 600 V, 2 line side lug, 2 load side lug, CU lug, rail mount



Main

Range of Product	NSYEB	
Product or Component Type	Power Distribution Block	

Complementary

Complementary	
[Ue] rated operational voltage	600 V AC/DC
Line Rated Current	510 A copper
Mounting Support	35 mm DIN rail
Electrical connection	Tin plated copper lugs
Number of terminals	2 line 2 load
Number of cables	Line 2, AWG 6250 kcmil, copper Load 2, AWG 6250 kcmil, copper
Short-circuit current	10 kA
Material	Thermoplastic: block
Colour of enclosure	Grey
Wire stripping length	Line: 1.38 in (35.05 mm) Load: 1.38 in (35.05 mm)
Connections - terminals	Line lug 275 lbf.in (31.07 N.m) AWG 1250 kcmil copper Line lug 120 lbf.in (13.56 N.m) AWG 6AWG 2 copper Load lug 275 lbf.in (31.07 N.m) AWG 1250 kcmil copper Load lug 120 lbf.in (13.56 N.m) AWG 6AWG 2 copper
Height	4.39 in (111.51 mm)
Tightening torque	Line 275 lb.in, AWG 1250 kcmil, copper Line 120 lb.in, AWG 6AWG 2, copper Load 275 lb.in, AWG 1250 kcmil, copper Load 120 lb.in, AWG 6AWG 2, copper
Width	2.26 in (57.40 mm)
Depth	3.14 in (79.76 mm)
Product compatibility	NSYEBP250 250 kcmil) NSYEBP500 500 kcmil)

Environment

Product Certifications	UL recognized E60616 CCN XCFR2[RETURN]CE[RETURN]CSA file 70361 class 6228 01
Dielectric strength	1000 V 0.19 in² (120 mm²) IEC 60947-7-1
Ambient Air Temperature for Operation	-40257 °F (-40125 °C)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherent for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the dourn and restring of the products with respect to the relevant specific application or use thereof. Neither Schmeider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Ordering and shipping details

21713-IEC ENCLOSED POWER DISTR BLOCKS
CP1
785901566137
No
US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	31.52 oz (893.577 g)

Offer Sustainability

REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant EPEU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.