



## Overview

Lead time	Usually in Stock
-----------	------------------



## Main

Main Input Voltage	208 V
Main Output Voltage	208 V
Number of rack unit	3U
Number of cables	1.0
Battery Type	Lead-Acid battery
Provided Equipment	Installation guide Rack Mounting brackets User Manual

## Batteries & Runtime

Battery blocks per string	16
Battery Slots Empty	0
Included Battery Modules	4
Battery manufacturer	Panasonic
Device mounting	Stand alone battery stack
Battery Voltage	192V
Additional information	Replace all batteries in operation together (UPS internal and external batteries) all-at-once
RBC Quantity	2

## Physical

Color	Black
Height	5.12 in (13 cm)
Width	17.01 in (43.2 cm)
Depth	25.98 in (66 cm)
Net Weight	200.42 lb(US) (90.91 kg)
Mounting Mode	Rack-mounted
USB compatible	No

## Conformance

Standards	OSHPD
-----------	-------

## Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Operating altitude	0...10000 ft
Relative Humidity	0...95 % non-condensing
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)
Storage Relative Humidity	0...95 % non-condensing

## Ordering and shipping details

GTIN	731304259336
------	--------------

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	16.26 in (41.3 cm)
Package 1 Width	39.37 in (100 cm)
Package 1 Length	23.62 in (60 cm)
Package 1 Weight	223.46 lb(US) (101.36 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
Take-back	Take-back program available

## Contractual warranty

Warranty	2 years repair or replace, optional on-site warranties available, optional extended warranties available
----------	--