

## LK4DU3CN

Disconnect Switch, TeSys LK4 Non fusible,  
25hp at 600VAC, 3 pole, max 32A rated, plate  
mount



### Main

Range	TeSys
Product name	TeSys LK
Product or Component Type	Disconnect Switch
Disconnecter device type	Non-fusible disconnect switch
Suitability for isolation	Yes

### Complementary

Poles description	3P
Network type	AC
Network Frequency	50/60 Hz
[Ie] rated operational current	32 A400 V AC AC-22A IEC 32 A400 V AC AC-23A IEC 32 A690 V AC AC-22A IEC 32 A690 V AC AC-23A IEC 30 A CSA 30 A UL
[Ue] rated operational voltage	600 V AC 50/60 Hz
[Ui] Rated Insulation Voltage	690 V
Control type	Rotary handle
Type of operating handle	External frontal External right side
Mounting Support	Plate
[Uimp] rated impulse withstand voltage	8 kV IEC
Rated power in W	15 KW 400 V 18.5 KW 500 V 25 kW 690 V
Rated power in hp	10 Hp 240 V 30 A AC 20 Hp 480 V 28 A AC 25 hp 600 V 28 A AC
[Icw] rated short-time withstand current	5.5 kA
Mechanical durability	10000 cycles
Electrical durability	6000 cycles
Connections - terminals	Lugs-ring terminals 1 0.01 in <sup>2</sup> (4 mm <sup>2</sup> )
Height	4.92 in (125 mm)
Width	3.13 in (79.5 mm)
Depth	2.52 in (64 mm)

### Environment

Standards	UL98 IEC 60947-3 CSA C22.2 No 4
Product Certifications	CE[RETURN]CSA[RETURN]UL

## Ordering and shipping details

Category	22640-IEC DISCONNECT-GS1,LK3
Discount Schedule	I11
GTIN	3606480510410
Returnability	Yes
Country of origin	CN

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	3.27 in (8.3 cm)
Package 1 Width	3.54 in (9.0 cm)
Package 1 Length	6.30 in (16.0 cm)
Package 1 Weight	21.94 oz (622.0 g)
Unit Type of Package 2	S03
Number of Units in Package 2	18
Package 2 Height	11.81 in (30.0 cm)
Package 2 Width	11.81 in (30.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	25.91 lb(US) (11.754 kg)

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Styrene, which is known to the State of California to cause cancer. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
RoHS exemption information	<a href="#">Yes</a>

## Contractual warranty

Warranty	18 months
----------	-----------