

Product data sheet

Characteristics

8940SSD4030V02S

Pump Panel, NEMA Type S, Well Guard, Size 2, 45A, 5kA SSCR, 30HP, 60A Class H and K fuse clip, Motor Logic SSOLR, 110/120VAC 50/60Hz coil, NEMA 3R



Main

Product	Well-Guard Control
Type	class 8940 type SS
Device Application	Pumping

Complementary

Control Circuit Type	Separate control circuit
Control Circuit Voltage	120 V AC 60 Hz 110 V AC 50 Hz
Line Rated Current	45 A
Number of Poles	3
Horsepower Rating	30 hp 480 V AC, 3 phase
Maximum Voltage Rating	600 V AC
Control Units	Selector switch HAND-OFF-AUTO) Push-button START)
Disconnect Type	Fusible disconnect switch
Associated fuse rating	60 A
Fuse type	H or K
Thermal overload type	Motor Logic solid state class 10/20
Protection Type	Overload Phase loss Phase unbalance
Device mounting	Surface
Electrical Connection	Screw terminal
NEMA size	2
Height	39.06 in (992 mm)
Width	15.16 in (385 mm)
Depth	9.69 in (246 mm)

Environment

NEMA Rating	NEMA 3R
Enclosure type	Weatherproof enclosure indoor/outdoor
Product Certifications	UL Listed[RETURN]NEMA

Ordering and shipping details

Category	21388-8940 NSC,NSD
Discount Schedule	CP1
GTIN	785901150428
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	39.06 in (99.2 cm)
Package 1 Width	15.16 in (38.5 cm)
Package 1 Length	9.69 in (24.6 cm)
Package 1 Weight	71.00 lb(US) (32.205 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	China RoHS Declaration
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------