



### Main

Range of product	Multi9
Product or Component Type	Connector
Accessory / separate part category	Connection accessory
Quantity per Set	Set of 4

### Complementary

Line Rated Current	63 A
[Ui] Rated Insulation Voltage	1000 V
Connection pitch	0.71 in (18 mm)
Standards	UL 486E
Product certifications	CURus[RETURN]IEC
Color	White RAL 9001)
Connections - terminals	Screw terminal top connector 0.01...0.05 in <sup>2</sup> (6...35 mm <sup>2</sup> ) rigid Screw terminal top connector 0.01...0.05 in <sup>2</sup> (6...35 mm <sup>2</sup> ) flexible
Tightening torque	30.98 lbf.in (3.5 N.m)
Range compatibility	Multi9 Multi9 C60 C60BP comb busbar

### Ordering and shipping details

Category	00949-M9 GEN 2 CB UL489
Discount Schedule	DE2
GTIN	3606481192851
Returnability	Yes
Country of origin	DE

### Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.22 in (3.100 cm)
Package 1 Width	3.58 in (9.100 cm)
Package 1 Length	4.41 in (11.200 cm)
Package 1 Weight	4.90 oz (139 g)
Unit Type of Package 2	S02
Number of Units in Package 2	25
Package 2 Height	5.91 in (15.000 cm)
Package 2 Width	11.81 in (30.000 cm)
Package 2 Length	15.75 in (40.000 cm)
Package 2 Weight	8.44 lb(US) (3.830 kg)

## Offer Sustainability

REACH Regulation	 <a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>
RoHS exemption information	 <a href="#">Yes</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.