8536SDG1V03H30

NEMA motor starter, Type S, nonreversing, Size 2, 45A, 25HP at 460VAC, up to 100kA SCCR, 3 phase, 3 pole, Motor Logic, 240VAC coil, NEMA 1



Main

Product Type	Motor starter
Product Range	S
Starter Type	Non reversing

Complementary

NEMA Size	2	
Rated Current	45 A	
Number of Poles	3P	
Maximum Voltage Rating	600 V AC	
Phase	3 phase	
Type of Overload	Solid state Motor Logic class 10/20	
Horsepower Rating	10 HP 200 V AC 15 HP 230 V AC 25 HP 460 V AC 25 HP 575 V AC	
SCCR	Circuit-breaker 100 A maximum: 100 kA at 480 V AC Fuse J 100 A maximum: 100 kA at 600 V AC Fuse T 100 A maximum: 100 kA at 600 V AC Fuse RK1 100 A maximum: 100 kA at 600 V AC Fuse RK5 100 A maximum: 100 kA at 600 V AC	
Coil Voltage	220 V AC 50 Hz 240 V AC 60 Hz	
Control Circuit Type	Common control circuit	
Control Units	No control units	
Pilot Light	Without pilot light	
Auxiliary Contacts	Without	
Terminal Type	Screw clamp terminals	
Height	12.69 in (322.33 mm)	
Width	7.81 in (198.37 mm)	
Depth	6.31 in (160.27 mm)	

Environment

Enclosure Type	NEMA 1 painted sheet steel	
Certifications	UL Listed[RETURN]CSA[RETURN]NEMA	

Ordering and shipping details

Category	21192-8502,36 SC,SD(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	785901807070
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.40 in (23.876 cm)
Package 1 Width	13.40 in (34.036 cm)
Package 1 Length	14.60 in (37.084 cm)
Package 1 Weight	13.20 lb(US) (5.987 kg)

Offer Sustainability

<u> </u>	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	€Yes
PVC free	Yes

Contractual warranty

To the detail that tall the terms of the ter		
Warranty	18 months	