



ALTERNATE LUG QUANTITY PER LINE SIDE PHASE AND NEUTRAL TERMINALS (ORDER SEPARATELY)			
CATALOG NUMBER	ANDERSON		ILSCO
	VHCL-600-12BN	VHCL-750-12BN	2ACL-600
	250-600 CU	500-750 CU	250-600 AL/CU
	VC-6 ‡	VC-7 ‡	IDT-12
EZM31600GBCMS	6	6	6
EZM31600JBCMS	6	6	6

‡ INDICATED VERSA-CRIMP CRIMPING TOOL.

NO KNOCKOUTS PROVIDED

NOTES:  
 FINISH - GRAY BAKED ENAMEL POWDER COAT PAINT OVER CLEANED GALVANNEALED STEEL.  
 UL LISTED - FILE E131840, VOL. M  
 SUITABLE FOR USE AS SERVICE EQUIPMENT.  
 MAIN HORIZONTAL CROSS BUS RATED AT 1200 AMPERES.  
 MAIN DEVICES ARE SEALABLE BY UTILITY.  
 GANGABLE MULTI-METERING EQUIPMENT IS DESIGNED FOR WALL MOUNTING ONLY.  
 (NOT SUITABLE FOR FLOOR STANDING EQUIPMENT.)  
 NO USER CONFIGURATION REQUIRED FOR ERMS FUNCTION.  
 ERMS SWITCH PROVIDED WITH LOCKABLE COVER.  
 ERMS MODULE WIRING DIAGRAM AND REPLACEMENT PARTS PROVIDED ON ENCLOSURE DOOR

SYSTEM TYPE	MAIN RATING (AMPERES)	CATALOG NUMBER	MAIN CIRCUIT BREAKER (FACTORY INSTALLED)	LINE SIDE PHASE LUG WIRE RANGE FOR AL OR CU CONDUCTORS (SUPPLIED WITH BREAKER)	LINE SIDE NEUTRAL LUG WIRE RANGE FOR AL OR CU CONDUCTORS (FACTORY INSTALLED)	GROUND LUG WIRE RANGE (FACTORY INSTALLED)
3Ø 4W 208Y/120VAC OR 240/120VAC DELTA	1600 ●	EZM31600GBCMS EZM31600JBCMS	RGF36160U63AE1 RJF36160U63AE1	(6) 1/0-750 OR (12) 1/0-250	(6) 1/0-750 OR (12) 1/0-250	(1) #6-300

● 1600A MAIN CIRCUIT BREAKER DEVICE MUST BE CENTER MOUNTED.

DUAL DIMENSIONS: INCHES  
MILLIMETERS

EZ METER-PAK GANGABLE  
 MULTI-METERING EQUIPMENT  
 1600A, 3PH 4W MAIN CIRCUIT BREAKER DEVICE  
 OVERHEAD/UNDERGROUND FEED  
 RAINPROOF NEMA TYPE 3R ENCLOSURE

**SQUARE D**™  
 by Schneider Electric

DWG# PWFDS-SYRS-0117  
 NO.