Product data sheet Characteristics

QO612L100TRB

Load center, QO, 1 phase, 6 spaces, 12 circuits, 100A fixed main lugs, NEMA3R, gnd bar, UL





Main

Marketing Trade Name	QO
Product Type	Load Center
Enclosure Type	Weatherproof enclosure
Cover Type	Surface cover

Complementary

Complementary		
Tightening Torque	Main lugs 50 lb.in, AWG 8, aluminium/copper Main lugs 50 lb.in, AWG 6AWG 1/0, aluminium/copper	
PoN Convertible Mains (lugs)	Fixed Mains (lugs)	
Rated Current	100 A	
Number of Spaces	6	
Max Short Circuit Current Rating	10 kA	
Maximum Number of Single Pole Circuits	12	
Maximum Number of Tandem Breakers	6	
Number of Phases	1 phase	
Voltage Rating	120/240 V AC	
Wire Size	AWG 8AWG 1 aluminium/copper	
Ground Bar	Grounding bar (factory installed)	
Electrical Connection	Lugs	
Wiring Configuration	3-wire	
Busbar Material	Tin plated aluminium: busbar	
Enclosure Material	Welded galvannealed steel	
Surface Finish	Baked enamel Gray	
Box Number	2R	
Height	12.44 in (316 mm)	
Width	8.90 in (226 mm)	
Depth	4.02 in (102 mm)	
Net Weight	9.26 lb(US) (4.200 kg)	

Environment

Enclosure Rating	NEMA 3R outdoor
Ambient Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)
Product Certifications	UL Listed

Ordering	and	shin	nina	detai	le
Ordering	anu	SHIP	pirig	uctai	ıo

Category	00101-QO 1PH LC,2-8CKT,NEMA 1,3R
Discount Schedule	DE3A
GTIN	785901119500
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	4.90 in (12.446 cm)
Package 1 Width	10.10 in (25.654 cm)
Package 1 Length	14.20 in (36.068 cm)
Package 1 Weight	9.69 lb(US) (4.395 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	☑ China RoHS Declaration
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months