Product data sheet Characteristics

8702SGG3V03

NEMA Contactor, Type S, reversing, horizontal, Size 5, 270A, 200 HP at 575 VAC, 3 phase, up to 100 kA, 3 pole, 240 VAC coil, NEMA 1



Main

Product Type	Contactor	
Product Range	Type S	
Contactor Type	Reversing	

Complementary

Complementary		
NEMA Size	5	
Rated Current	270 A	
Number of Poles	3P	
Mounting Orientation	Horizontal	
Wiring Mode	3 wires	
Maximum Voltage Rating	600 V AC	
Phase	3 phase	
Horsepower Rating	75 HP 200 V AC 100 HP 230 V AC 200 HP 460 V AC 200 HP 575 V AC	
SCCR	Circuit-breaker 400 A maximum, SCCR: 100 kA at 480 V AC Fuse J 400 A maximum, SCCR: 100 kA at 600 V AC Fuse T 400 A maximum, SCCR: 100 kA at 600 V AC Fuse RK1 400 A maximum, SCCR: 100 kA at 600 V AC Fuse RK5 400 A maximum, SCCR: 100 kA at 600 V AC	
Coil Voltage	220 V AC 50 Hz 240 V AC 60 Hz	
Control Circuit Type	Common control circuit	
Control Units	No control units	
Pilot Light	No indicator	
Other Equipment	Fuse not supplied	
Terminal Type	Screw clamp terminals	
Height	46.22 in (1173.99 mm)	
Width	35.22 in (894.59 mm)	
Depth	12.81 in (325.37 mm)	

Environment

Enclosure Type	NEMA 1 painted sheet steel
Certifications	UL Listed[RETURN]CSA

Ordering and shipping details

Category	21274-8702,36SG(NOT S*R,S*T,S*W)
Discount Schedule	CP1
GTIN	3606482141094
Returnability	No
Country of origin	MX

Packing Units

PCE
1
46.22 in (117.4 cm)
35.24 in (89.5 cm)
12.80 in (32.5 cm)
265.00 lb(US) (120.202 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
EU RoHS Directive	Not compliant	

Contractual warranty

	•
Warranty	18 months