



**Note:**  
 - Drawings Not To Scale  
 - Drawings Subject to Change Without Notice  
 - Dimensions are inches next to [Millimeters]

Part No.:  
**PJL36060**



Schneider Electric United States  
 North American Division  
 Boston One Campus  
 800 Federal Street  
 Andover, MA 01810, USA  
 Phone: +1 8773425173  
 Email: CCC@us.schneider-electric.com

**Technical Information:**

General Application:	Provides overload and short circuit protection
For Use With:	Panelboards and Switchboards
Approvals:	UL Listed - CSA Certified - IEC Rated
Mounting Type:	Unit Mount
Terminal Type:	Lugs (ON and OFF ends)
Wire Size:	#3/0-500 AWG/kcmil(Al/Cu)
Weight:	32 Pounds
Depth:	8.07 Inches
Height:	12.86 Inches
Width:	8.27 Inches

<b>Description:</b>	PowerPact P-frame Electronic Trip Circuit Breaker
<b>Number of Poles:</b>	3-Pole
<b>Sensor Rating:</b>	600A
<b>Voltage Rating:</b>	600VAC
<b>Interrupting Rating:</b>	100kA at 240VAC - 65kA at 480VAC - 25kA at 600VAC
<b>Circuit Breaker Rating:</b>	80% Rated
<b>Electronic Trip Unit:</b>	Basic (ET1.0I)
<b>Trip Function:</b>	Fixed Long-Time Adjustable Instantaneous Trip
<b>Installed Rating Plug:</b>	
<b>Rating Plug Range:</b>	

**Specification:**