



Main

| | |
|-----------------------------|---------------------------|
| Product or Component Type | Miniature circuit-breaker |
| Range of Product | QOU |
| Circuit breaker type | Standard |
| Circuit breaker application | HACR rated |

Complementary

| | |
|--------------------------------|--|
| Line Rated Current | 10 A |
| Electrical connection | Ring tongue, line side Ring tongue, load side |
| [Ue] rated operational voltage | 120/240 V AC 240 V AC 120 V AC 48 V DC |
| Mounting Mode | Unit mount |
| AWG gauge | AWG 14...AWG 2 aluminium/copper |
| Height | 4.05 in (102.87 mm) |
| Width | 2.25 in (57.15 mm) |
| Depth | 2.95 in (74.93 mm) |
| Tightening torque | 45 lbf.in (5.08 N.m) (AWG 14...AWG 2) |

Environment

| | |
|------------------------|---------------------------------|
| Product Certifications | CSA[RETURN]UL Listed[RETURN]IEC |
|------------------------|---------------------------------|

Ordering and shipping details

| | |
|-------------------|-----------------------------|
| Category | 00900-QOU BREAKERS & SWITCH |
| Discount Schedule | DE2 |
| GTIN | 785901630852 |
| Returnability | Yes |

Packing Units

| | |
|------------------------------|------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 3.50 in (8.89 cm) |
| Package 1 Width | 2.60 in (6.604 cm) |
| Package 1 Length | 4.90 in (12.446 cm) |
| Package 1 Weight | 1.14 lb(US) (0.517 kg) |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

| | |
|-----------------------------|--|
| Sustainable offer status | Green Premium product |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant with Exemptions |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | China RoHS Declaration |
| RoHS exemption information | Yes |
| Circularity Profile | No need of specific recycling operations |
| Halogen content performance | Halogen free product |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|