MPH66125

Meter center, MP Meter-Pak, 6 sockets, horn bypass, 5 jaws, 600A bus, 125A max breaker rating, ringless



Main

| Main | | |
|----------------------------|--------------|--|
| Product | Meter Center | |
| Socket Rating | 125 A | |
| Main Type | Main Lugs | |
| Number of Jaws | 5 | |
| Number of Meter Sockets | 6 | |
| Socket Type Ringless | | |

Complementary

| Main Rating | 500 A 400 A | |
|------------------------|---|--|
| Bus Rating | 600 A | |
| Certifications | UL Listed | |
| Туре | Meter-Pak | |
| Busbar Material | Aluminium: busbar | |
| Bypass Type | Horn bypass | |
| Enclosure Material | Steel | |
| Enclosure Rating | NEMA 3R | |
| Maximum Voltage Rating | 120/240 V AC | |
| Mounting | Surface | |
| Phase | 1 phase | |
| Service Feed Location | UG OH | |
| Wire Size | AWG 1/0600 kcmil 1 aluminium AWG 1/0600 kcmil 1 copper | |
| Wire Configuration | 3-wire | |

Ordering and shipping details

| Category | 00021-METER-PAK |
|-------------------|-----------------|
| Discount Schedule | DE4 |
| GTIN | 785901208143 |
| Returnability | Yes |
| Country of origin | MX |

Packing Units

| PCE | |
|---------------------------|---|
| 1 | |
| 8.50 in (21.6 cm) | |
| 36.89 in (93.7 cm) | |
| 43.19 in (109.7 cm) | |
| 132.00 lb(US) (59.874 kg) | |
| | 1 8.50 in (21.6 cm) 36.89 in (93.7 cm) 43.19 in (109.7 cm) |

Offer Sustainability

| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
|----------------------------|---|
| REACh Regulation | ☑ REACh Declaration |
| REACh free of SVHC | Yes |
| EU RoHS Directive | Compliant EPEU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| China RoHS Regulation | ☑ China RoHS Declaration |
| RoHS exemption information | €Yes |

Contractual warranty

| 14/ | 40 months |
|-----------|---------------|
| vvarranty | 18 months |
| | |