Product data sheet Characteristics

9070TF200D1

Industrial control transformer, Type TF, 1 phase, 200VA, 240x480V primary, 120V secondary, 50/60Hz





Product or Component Type	Industrial Control Transformer
Туре	TF

Complementary

Number of Phases	1 phase
Power Rating	200 VA UL[RETURN]200 VA CSA[RETURN]200 VA NOM[RETURN]200 VA CE
Primary to Secondary Voltage	240 x 480 V 120 V 230 x 460 V 115 V 220 x 440 V 110 V
Fuse type	0.41 x 1.50 in CC top
Temperature rise	80 °C
Electrical Connection	Screw clamp terminals
Height	4.5 in (114.30 mm)
Width	3.75 in (95.25 mm)
Depth	3.59 in (91.19 mm)
Material	Copper: winding
Fingersafe Cover Compatibility	FSC1
Environment Product Certifications	CSA file LR37055 guide 184-N-90[RETURN]UL listed file E61239
Product Certifications	CSA file LR37055 guide 184-N-90[RETURN]UL listed file E61239
Enclosure Type	Not rated (open device)
Insulation temperature	266 °F (130 °C)
Ordering and shipping details	
Category	16202-9070 TF (NOT T) 50-200VA
Discount Schedule	CP8
GTIN	785901904809
Returnability	Yes
Country of origin	MX
Packing Units	
Unit Type of Package 1	PCE

Unit Type of Package 1PCENumber of Units in Package 11Package 1 Height4.55 in (11.557 cm)Package 1 Width3.60 in (9.144 cm)Package 1 Length3.75 in (9.525 cm)



Package 1 Weight	6.35 lb(US) (2.88 kg)
Unit Type of Package 2	PAL
Number of Units in Package 2	150
Package 2 Height	40.00 in (101.6 cm)
Package 2 Width	40.00 in (101.6 cm)
Package 2 Length	48.00 in (121.92 cm)
Package 2 Weight	953.00 lb(US) (432.273 kg)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	REACh Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	₫ Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
PVC free	Yes

Contractual warranty

Warranty

18 months