## Product data sheet Characteristics

# RC816F150C

Meter mains, Homeline, CSED, ringless socket, 150A, surface mount, maximum 8 spaces, 16 circuits, no bypass





Main		
Product or Component Type	Meter Mains	
Range of Product	Homeline	

Complementary

Complementary		
Line Rated Current	150 A	
Short-circuit current	22 kA	
Network number of phases	1	
Meter socket type	Ringless	
Mounting	Surface	
Number of spaces	8	
Number of circuits	16	
Number of Tandem Breakers	8	
Hub type	A	
Electrical connection	Lugs, line side Feed-thru lugs, service ground	
Wire Size	AWG 6350 kcmil aluminium/copper)line side AWG 12AWG 2/0 aluminium/copper)service ground	
Tightening torque	Main lugs 250 lb.in, AWG 6350 kcmil, aluminium/copper Service ground 50 lb.in, AWG 14AWG 2/0, copper Service ground 50 lb.in, AWG 12AWG 2/0, aluminium Branch lugs 35 lb.in, AWG 6AWG 4, aluminium/copper Branch lugs 25 lb.in, AWG 8, aluminium/copper Branch lugs 20 lb.in, AWG 14AWG 10, copper Branch lugs 20 lb.in, AWG 12AWG 10, aluminium Cover 10 lb.in	
Disconnect	Service disconnect (factory installed)	
Main Breaker Rating	150 A	
Branch Breaker Rating	150 A	
Service feed location	OH UG	
Bypass type	No bypass	
Height	35.13 in (892.30 mm)	
Width	14.37 in (365.00 mm)	
Depth	5.07 in (128.78 mm)	
Bus Rating	200.0 A	

#### Environment

Product certifications UL E-6294		
	Product certifications	UL E-6294

Ordering	and	shin	nina	detai	le
Ordering	anu	SHIP	pirig	uctai	ıo

Category	00048-HOM METER MAINS
Discount Schedule	DE3A
GTIN	785901859192
Returnability	Yes
Country of origin	MX

### Packing Units

PCE
1
5.80 in (14.732 cm)
15.00 in (38.1 cm)
36.80 in (93.472 cm)
42.54 lb(US) (19.296 kg)

#### Offer Sustainability

Green Premium product	
WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	
☑ REACh Declaration	
Compliant with Exemptions	
Yes	
☑ China RoHS Declaration	
€Yes	
Product Environmental Profile	
No need of specific recycling operations	

#### Contractual warranty

Warranty	18 months