Product data sheet Characteristics

9065SFB20

Overload Relay, Motor Logic, solid state overload relay, NEMA Size 00, 3 pole, 1.5A to 4.5A, 600VAC, separate mount





Main

Range of Product	Motor Logic
Thermal overload type	Solid state

Complementary

Complementary		
NEMA size	00	
Phase	3 phase	
Mounting Support	Mounting plate	
[Ue] rated operational voltage	600 V AC	
Height	2.69 in (68.3 mm)	
Width	3.26 in (82.8 mm)	
Depth	3.90 in (99.1 mm)	

Ordering and shipping details

Category	21662-9065 SOLID STATE OVERLOAD RELAYS	
Discount Schedule	CP1	
GTIN	785901039686	
Returnability	Yes	
Country of origin	MX	

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	5.31 in (13.5 cm)	
Package 1 Width	5.39 in (13.7 cm)	
Package 1 Length	6.10 in (15.5 cm)	
Package 1 Weight	15.36 oz (435.4 g)	

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑REACh Declaration
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or intellability of these products for specific user applications. It is the doung nation such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

China RoHS Regulation	China RoHS Declaration	
RoHS exemption information	₫Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	☑ End Of Life Information	
PVC free	Yes	

Contractual warranty

	•
Warranty	40
Warranty	18 months
•	