# 8536SBO2V08S

NEMA Motor Starter, Type S, nonreversing, Size 0, 18A, 5 HP at 460 VAC, 5 kA SCCR, 3 phase, 3 pole, melting alloy, 208 VAC coil, open



#### Main

Product Type	Motor starter
Product Range	S
Starter Type	Non reversing

Complementary

NEMA Size         0           Rated Current         18 A           Number of Poles         3P           Maximum Voltage Rating         600 V AC           Phase         3 phase           Type of Overload         Melting alloy 3           Horsepower Rating         3 HP 200 V AC           3 HP 230 V AC         5 HP 460 V AC           5 HP 575 V AC           SCCR         Circuit-breaker: 5 kA at 600 V AC           Fuse: 5 kA at 600 V AC           Coil Voltage         208 V AC 60 Hz           Control Circuit Type         Separate control circuit           Control Units         No control units			
Number of Poles         3P           Maximum Voltage Rating         600 V AC           Phase         3 phase           Type of Overload         Melting alloy 3           Horsepower Rating         3 HP 200 V AC 3 HP 230 V AC 5 HP 460 V AC 5 HP 575 V AC           SCCR         Circuit-breaker: 5 kA at 600 V AC Fuse: 5 kA at 600 V AC           Coil Voltage         208 V AC 60 Hz           Control Circuit Type         Separate control circuit	NEMA Size	0	
Maximum Voltage Rating 600 V AC  Phase 3 phase  Type of Overload Melting alloy 3  Horsepower Rating 3 HP 200 V AC 3 HP 230 V AC 5 HP 460 V AC 5 HP 575 V AC  SCCR Circuit-breaker: 5 kA at 600 V AC Fuse: 5 kA at 600 V AC  Coil Voltage 208 V AC 60 Hz  Control Circuit Type Separate control circuit	Rated Current	18 A	
Phase 3 phase  Type of Overload Melting alloy 3  Horsepower Rating 3 HP 200 V AC 3 HP 230 V AC 5 HP 460 V AC 5 HP 575 V AC  SCCR Circuit-breaker: 5 kA at 600 V AC Fuse: 5 kA at 600 V AC  Coil Voltage 208 V AC 60 Hz  Control Circuit Type Separate control circuit	Number of Poles	3P	
Type of Overload  Horsepower Rating  3 HP 200 V AC 3 HP 230 V AC 5 HP 460 V AC 5 HP 575 V AC  SCCR  Circuit-breaker: 5 kA at 600 V AC Fuse: 5 kA at 600 V AC  Coil Voltage  208 V AC 60 Hz  Control Circuit Type  Separate control circuit	Maximum Voltage Rating	600 V AC	
Horsepower Rating  3 HP 200 V AC 3 HP 230 V AC 5 HP 460 V AC 5 HP 575 V AC  SCCR  Circuit-breaker: 5 kA at 600 V AC Fuse: 5 kA at 600 V AC  Coil Voltage  208 V AC 60 Hz  Control Circuit Type  Separate control circuit	Phase	3 phase	
3 HP 230 V AC 5 HP 460 V AC 5 HP 575 V AC  SCCR  Circuit-breaker: 5 kA at 600 V AC Fuse: 5 kA at 600 V AC  Coil Voltage  208 V AC 60 Hz  Control Circuit Type  Separate control circuit	Type of Overload	Melting alloy 3	
Fuse: 5 kA at 600 V AC  Coil Voltage 208 V AC 60 Hz  Control Circuit Type Separate control circuit	Horsepower Rating	3 HP 230 V AC 5 HP 460 V AC	
Control Circuit Type Separate control circuit	SCCR		
	Coil Voltage	208 V AC 60 Hz	
Control Units No control units	Control Circuit Type	Separate control circuit	
	Control Units	No control units	
Pilot Light Without pilot light	Pilot Light	Without pilot light	
Auxiliary Contacts Without	Auxiliary Contacts	Without	
Terminal Type Screw clamp terminals	Terminal Type	Screw clamp terminals	
Height 6.81 in (172.96 mm)	Height	6.81 in (172.96 mm)	
Width 3.50 in (88.90 mm)	Width	3.50 in (88.90 mm)	
Depth 4.22 in (107.19 mm)	Depth	4.22 in (107.19 mm)	

### Environment

Enclosure Type	Not rated (open device)
Certifications	UL Listed[RETURN]CSA[RETURN]NEMA

### Ordering and shipping details

Category	21191-8502,36 SA,SB(NOT S*R,T,W)
Discount Schedule	CP1
GTIN	785901812531
Returnability	No
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.81 in (17.3 cm)
Package 1 Width	3.50 in (8.9 cm)
Package 1 Length	4.21 in (10.7 cm)
Package 1 Weight	4.00 lb(US) (1.814 kg)

### Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Not compliant
China RoHS Regulation	☑ China RoHS Declaration
PVC free	Yes

### Contractual warranty

Warranty	18 months

### **Approximate Dimensions**

