

Main

Range of Product	TeSys
Product name	TeSys D
Product or Component Type	Contacteur
Device short name	LC1D
Contacteur application	Lighting
Poles description	3P
Power pole contact composition	3 NO
[Ue] rated operational voltage	600 V AC 50/60 Hz
[Ie] rated operational current	Tungsten: 100 A at 480 V AC Ballast: 100 A at 600 V AC
[Uc] control circuit voltage	240 V AC 50/60 Hz
Mounting Support	Rail Plate
Standards	NEMA UL

Environment

Height	5.00 in (127 mm)
Width	3.35 in (85 mm)
Depth	5.12 in (130 mm)



Ordering and shipping details

Category	22359-CTR, TESYS D, OPEN, 80-150A AC&DC
Discount Schedule	I12
GTIN	785901003441
Returnability	Yes

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	5.00 in (12.7 cm)
Package 1 Width	3.35 in (8.5 cm)
Package 1 Length	5.12 in (13.0 cm)
Package 1 Weight	3.44 lb(US) (1.56 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
RECh Regulation	 RECh Declaration
RECh free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes

China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes
PVC free	Yes
