SSP02XDSE10A

Surge protection device, XDSE, 100kA, 208Y/120 VAC, 3 phase, 4 wire, SPD type 2



Main
Product

Surge protection device

Complementary

e emplementar y		
Voltage Rating	208Y/120 V AC	
MCOV	150 V	
Surge Current	100 A per phase	
Voltage Protection Rating	700 V L-N 700 V L - G 600 V L - L 1000 V N - G	
Rated Current	20 kA	
Number of Phases	3 phase	
Wiring Configuration	4-wire	
Height	5.98 in (152 mm)	
Width	5.98 in (152 mm)	
Depth	3.98 in (101 mm)	

Environment

Enclosure Rating	NEMA 4X

Ordering and shipping details

Category	08466-SURGE PROTECTION HWA
Discount Schedule	DE1B
GTIN	785901085041
Returnability	Yes
Country of origin	MX

Packing Units

U		
Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Height	5.98 in (15.2 cm)	
Package 1 Width	5.98 in (15.2 cm)	
Package 1 Length	3.98 in (10.1 cm)	
Package 1 Weight	3.91 lb(US) (1.774 kg)	

Offer Sustainability	
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Compliant with Exemptions
Mercury free	Yes
China RoHS Regulation	China RoHS Declaration
RoHS exemption information	Yes