

## Product data sheet

### Characteristics

# 8940WE3S2V02H30S

Pump Panel, NEMA Type S, Well Guard, oil field, Size 3, 90A, 50HP, 100A fusible disconnect, Motor Logic SSOLR, 110/120VAC 50/60Hz coil, NEMA 3R



### Main

Product	Well-Guard Control
Type	S2
Device Application	Pumping

### Complementary

Control Circuit Type	Separate control circuit
Control Circuit Voltage	120 V AC 60 Hz 110 V AC 50 Hz
Line Rated Current	90 A
Number of Poles	3
Horsepower Rating	50 hp 480 V AC, 3 phase
Maximum Voltage Rating	600 V AC
Control Units	Selector switch HAND-OFF-AUTO)
Disconnect Type	Fusible disconnect switch
Associated fuse rating	100 A
Fuse type	H or K
Thermal overload type	Motor Logic solid state class 10/20
Protection Type	Overload Phase loss Phase unbalance
Device mounting	Surface
Electrical Connection	Screw terminal
NEMA size	3
Height	56.50 in (1435 mm)
Width	24.49 in (622 mm)
Depth	10.31 in (262 mm)

### Environment

NEMA Rating	NEMA 3R
Enclosure type	Weatherproof enclosure indoor/outdoor
Product Certifications	UL Listed[RETURN]NEMA

### Ordering and shipping details

Category	21397-8940 WE,WF
Discount Schedule	CP1
GTIN	785901707257
Returnability	No
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	56.50 in (143.5 cm)
Package 1 Width	24.49 in (62.2 cm)
Package 1 Length	10.31 in (26.2 cm)
Package 1 Weight	182.00 lb(US) (82.554 kg)

## Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
EU RoHS Directive	Under investigation
China RoHS Regulation	 <a href="#">China RoHS Declaration</a>

## Contractual warranty

Warranty	18 months
----------	-----------