



Note:
 - Drawings Not To Scale
 - Drawings Subject to Change Without Notice
 - Dimensions are inches next to [Millimeters]

Part No.:

PKL36060U44A



by **Schneider Electric**

Schneider Electric United States
 North American Division
 Boston One Campus
 800 Federal Street
 Andover, MA 01810, USA
 Phone: +1 8773425173
 Email: CCC@us.schneider-electric.com

Technical Information:

General Application: Provides overload and short circuit protection
For Use With: Panelboards and Switchboards
Approvals: UL Listed - CSA Certified - IEC Rated
Mounting Type: Unit Mount
Terminal Type: Lugs (ON and OFF ends)
Wire Size: #3/0-500 AWG/kcmil(Al/Cu)
Weight:
Depth: 8.07 Inches
Height: 12.86 Inches
Width: 8.27 Inches

Specification:

Description: PowerPact P-frame Electronic Trip Circuit Breaker
Number of Poles: 3-Pole
Sensor Rating: 600A
Voltage Rating: 600VAC
Interrupting Rating: 65kA at 240VAC - 50kA at 480/600VAC
Circuit Breaker Rating: 80% Rated
Electronic Trip Unit: Micrologic Ammeter Trip Unit (6.0A)
Trip Function: LSIG
Installed Rating Plug: Type A
Rating Plug Range: 0.4A to 1A