Product data sheet Characteristics

8940WF3S2V06A28H30

Pump Panel, NEMA Type S, Well Guard, oil field, Size 4, 135A, 100HP, 200A fusible disconnect, Motor Logic SSOLR, 440/480VAC 50/60Hz coil, NEMA 3R



Main

Product	Well-Guard Control
Туре	S2
Device Application	Pumping

Complementary

o o mpromornary		
Control Circuit Type	Common control circuit	
Control Circuit Voltage	480 V AC 60 Hz 440 V AC 50 Hz	
Line Rated Current	135 A	
Number of Poles	3	
Horsepower Rating	100 hp 480 V AC, 3 phase	
Maximum Voltage Rating	600 V AC	
Control Units	Selector switch HAND-OFF-AUTO) Push-button START)	
Disconnect Type	Fusible disconnect switch	
Associated fuse rating	400 A	
Fuse type	H or K	
Thermal overload type	Motor Logic solid state class 10/20	
Protection Type	Overload Phase loss Phase unbalance	
Device mounting	Surface	
Electrical Connection	Screw terminal	
NEMA size	4	
Height	56.50 in (1435 mm)	
Width	24.49 in (622 mm)	
Depth	10.31 in (262 mm)	

Environment

NEMA Rating	NEMA 3R
Enclosure type	Weatherproof enclosure indoor/outdoor
Product Certifications	UL Listed[RETURN]NEMA

Ordering and shipping details

Category	21397-8940 WE,WF
Discount Schedule	CP1
GTIN	785901466918
Returnability	No
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	56.50 in (143.5 cm)
Package 1 Width	24.49 in (62.2 cm)
Package 1 Length	10.31 in (26.2 cm)
Package 1 Weight	175.00 lb(US) (79.379 kg)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Under investigation

Contractual warranty

Warranty	18 months