



QQGQ2.E151273

Power Supplies, Information Technology Equipment Including Electrical Business Equipment - Component

[Page Bottom](#)

Power Supplies, Information Technology Equipment Including Electrical Business Equipment - Component

[See General Information for Power Supplies, Information Technology Equipment Including Electrical Business Equipment - Component](#)

SIEMENS AG

E151273

OESTERREICH

SIMEA

POSTFACH 83, SIEMENSSTRASSE 90

1211 VIENNA, AUSTRIA

	Rated Input			Max Output							
Model No.	Volts	Hz	SC	V	A	VA	OC	SP	EP	FC	GC
"LOGO! series".											
6EP1311-1SH02[*r]											
	100-240ac	50-60	0	5dc	3	18	3	60950	20B	5	2
6EP1311-1SH12[*r]											
	100-240ac	50-60	0	5dc	6.3	31.5	3	60950	20B	5	2
6EP1321-1SH02[*r]											
	100-240ac	50-60	0	12dc	1.9	22.8	3	60950	20B	5	2
6EP1322-1SH02[*r]											
	100-240ac	50-60	0	12dc	4.5	54	3	60950	20B	5	2
6EP1331-1SH02[*r]											
	100-240ac	50-60	0	24dc	1.3	31.2	1,3	60950	20B	5	2
6EP1332-1SH42[*r]											
	100-240ac	50-60	0	24dc	2.5	60	1,3	60950	20B	5	2
6EP1351-1SH02[*r]											
	100-240ac	50-60	0	15dc	1.9	28.5	3	60950	20B	5	2
6EP1352-1SH02[*r]											
	100-240ac	50-60	0	15dc	4	60	3	60950	20B	5	2
6EP-1332-2BA00 (+)(**)[*r]											
	120/ 230ac	50-60	0	24	3.8	92	1	1950	-	5	0
6EP1 336-3BA00											
	120/ 230ac	50/60	0	-	20	-	3	60950-1	10	5	1
6EP1311-1SH03[*r]											
	100-240ac	50/60	0	5dc	3	-	1	60950-1	20B	0	2
6EP1311-1SH13[*r]											
	100-240ac	50/60	0	5dc	6.3	-	3	60950-1	20B	0	2
6EP1321-1LD00											
	100-240ac	50-60	3	14.59dc	3.98	58.06	3	60950-1	20B	0	1

6EP1321-1SH03[*r]											
	100-240ac	50/60	0	12dc	1.9	-	1	60950-1	20B	0	2
6EP1322-1LD00											
	100-240ac	50-60	0	14.09dc	9.57	134.60	3	60950-1	20B	0	1
6EP1322-1SH03[*r]											
	100-240ac	50/60	0	12dc	4.5	-	1	60950-1	20B	0	2
6EP1331-1LD00											
	100-240 Vac	50-60	0	22.09dc	4.61	101.67	3	60950-1	20B	0	1
				24.07dc	4.79	114.77	3				
				28.59dc	5.16	146.8	3				
6EP1331-1SH03, 6EP1331-1SH02-0AA0, 6EP1331-1SH02-0SP0[*r]											
	100-240ac	50/60	0	24dc	1.3	-	1	60950-1	20B	0	2
6EP1331-2BA10											
	120-230ac	-	0	24.3	0.81	-	1	60950	15B	5	1
6EP1331-5BA00[*r]											
	100-230ac	50/60	0	24dc	0.6	-	1	60950-1	20B	0	1
6EP1331-5BA10[*r]											
	100-230ac	50/60	0	24dc	1.3	-	1	60950-1	20B	0	1
6EP1332-1LD00											
	100-240Vac	50-60	0	22.09dc	4.61	101.67	3	60950-1	20B	0	1
				24.07dc	4.79	114.77	3				
				28.59dc	5.16	146.8	3				
6EP1332-1LD10											
	100-240	-	0	24dc	4.1	100	3	60950-1	20B	0	1
6EP1332-1SH42-0AA0[*r]											
	100-240ac	50/60	0	-	2.5	-	1	60950-1	20B	0	2
6EP1332-1SH42-0SP0											
	100-240ac	50/60	0	-	2.5	-	3	60950-1	20B	0	2
6EP1332-1SH43[*r]											
	100-240ac	50/60	0	-	2.5	-	1	60950-1	20B	0	2
6EP1332-1SH51[*r]											
	100-240Vac, 120-250Vdc	47-63	0	24dc	4	96	3	60950-1	20B	5	0
6EP1332-1SH52[*r]											
	100-240ac	50/60	0	24dc	4	-	3	60950-1	20B	0	2
6EP1332-1SH61[*r]											
	100-240Vac, 120-250Vdc	47-63	0	24dc	3.5	84	3	60950-1	20B	5	0
6EP1332-1SH71 or PM 1207[*r]											
	120/ 230ac	50/60	0	24dc	2.5	-	1	60950-1	20B	5	1
6EP1332-5BA00[*r]											
	100-230ac	50/60	0	24dc	2.5	-	1	60950-1	20B	0	1
6EP1332-5BA20[*r]											
	100-230ac	50/60	0	24dc	3.7	-	1	60950-1	20B	0	1
6EP1333-1LD00											

	-	-	-	-	-	-	-	-	-	-	-
6EP1334-1LD00[*r]											
	100-240ac	50-60	0	24dc	12.5	300	3	60950-1	20B	0	1
6EP1336-2BA00											
	230/ 120Vac	50/60	0	-	-	-	-	60950-1	16A	5	1
6EP1351-1SH03[*r]											
	100-240ac	50/60	0	15dc	1.9	-	1	60950-1	20B	0	2
6EP1352-1SH03[*r]											
	100-240ac	50/60	0	15dc	4	-	1	60950-1	20B	0	2
6EP1436-0AA00											
	220-277/ 380-480ac	50/60	0	27.1	22.9	-	3	60950	25B	5	0
6EP1651-0AA20											
	27dc	-	3	5	3.3	-	3	60950	-	0	0
				3.3	3.5	-	3				
				24	0.5	-	3				
6EP1731-2BA00											
	48-220dc	-	0	24.3	0.41	-	1	60950	15B	5	1
6EP1931-0AA00[*r]											
	18-36dc	-	3	26	20	-	3	60950	-	0	0
6EP19612BA00											
	24dc	-	3	-	-	-	-	-	-	-	-
6EP1962-2BA00 (SITOP PSE202U)											
	24dc	-	3	-	3.93	89.8	1	60950-1	-	5	-
6EV3-035-7AC(c)(*)[*r]											
	10.5ac	50/60	2	5	6	-	4	1950	8	0	0
6EW-1811-8AA[*r]											
	24dc	-	4	3.3	4.2	135	3	1950	-	0	0
				5	10	-	3				
				12	1.7	-	3				
				-12	0.25	-	3				
				18	0.08	-	3				
6EW-1861-7AB(+)(*)[*r]											
	187-264ac	50-60	0	5	35	1500	3	1950	-	0	0
				5	220	-	3				
				12	40	-	3				
6EW-1881-8AA[*r]											
	120/ 230ac	50/60	0	3.3	4.2	135	3	1950	-	0	0
				5	10	-	3				
				12	1.7	-	3				
				-12	0.25	-	3				
				18	0.08	-	3				
6EW-1890-6AB(+)(*)[*r]											

	93-264ac	50-60	0	5	4	80	3	1950	-	0	0
				15	3	-	3				
				-15	1	-	3				
6EW-1890-6AC(+)(*)[*r]											
	93-264ac	50-60	0	5	8	100	3	1950	-	0	0
				15	3	-	3				
				-15	1	-	3				
6EW-1890-8AA(+)[*r]											
	120/ 230ac	47-63	0	3.3	2.2	65	3	1950	-	0	1
				5	8	-	3				
				12	1.5	-	3				
6EW1881-3AA(b)[*r]											
	120/ 240ac	50/60	0	5	10	-	4	1950 w/D3	-	0	0
				12	3	-	4				
6EW1881-4AA(b)[*r]											
	120/ 230ac	50/60	0	5	25	-	4	1950 w/D3	-	0	1
				12	3	-	4				
				28	0.32	-	4				
				100	0.4	-	4				
6EW1881-6AA(+)[*r]											
	120/ 230ac	47-63	0	12	2.5	79	3	1950	2	2	1
				5	10	91.35	3				
6EW1881-7AA											
	120/ 230ac	47-63	0	12	2	-	3	1950	2	2	1
				5	13	-	3				
				3.3	5	-	3				

[*r] - Output values are rated.

(*) - Complementary Recognized to QQIJ2.

(**) - Complementary Recognized to EPBU2.

(+) - Output power measured in watts.

(b) - Output not evaluated for continuous operation at values specified.

(c) - External input fuse, UL Recognized (JDYX2) rated 8 A, 250 V, manufactured by Bussman, Type B1302.

Marking: Company name and catalog designation on the product or on the smallest unit container in which the product is packaged.

Last Updated on 2013-02-08

[Questions?](#)

[Print this page](#)

[Terms of Use](#)

[Page Top](#)

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2013 UL LLC".